



| | | |
|---|-----------------------|---|
| C | Wire | Tinned copper |
| | Gauge | AWG 28/7 0,089 mm ² |
| | Voltage rating | 300 Vr.m.s |
| | Current rating | 2,1A at 25°C |
| | Capacity unbalanced | 45,9 pF/m at 1 MHz |
| | Impedance unbalanced | 105 Ω |
| | Propagation delay | 4,9 ns/m nominal |
| | Insulation material | PVC |
| | Temperature rating | -20°C (operating) -30°C (static) to +105°C |
| | Flammability rating | Flame retardant VW1 |
| B | Insulation resistance | 100 MΩ/km |
| | Approval | UL AWM style 2651 |

| | | | | | | | | | | | | | | | | | |
|--|--------------------|--|-------------------------------|------------------|----------------|--------------------|---|---|-------------------------------|---------------------------|--|--|--|--|--|--|--|
| A | | | | Dat. | | Name | |  All Dim. in mm Orig. Size DIN A 4 | SEK 18 flat cable 50 poles | Maßstab/ Scale 10:1 | | | | | | | |
| | | | | Detail. | 20/10/05 | JMDR | | | | | | | | | | | |
| | | | | Insp. | | | | | | | | | | | | | |
| | | | | Stand. | | | | | | | | | | | | | |
| | | | EC01360 | 19/02/10 | SC | |  | TB 09 18 050 700X | Blatt/ Page 1 / 1 | | | | | | | | |
| | | | 34400 | 18/09/07 | PK | | | | | | | | | | | | |
| | | | 33246 | 20/10/05 | JMDR | | | | | | | | | | | | |
| | | | Mod. | Dat. | Name | | | | | | | | | | | | |
| | | | HARTING EURL F-95972 Paris | | | | | | | | | | | | | | |
| <table border="1"> <tr> <td>09 18 050 7004</td> <td>100 m (328 feet)</td> </tr> <tr> <td>09 18 050 7001</td> <td>30,48 m (100 feet)</td> </tr> <tr> <td>Part number</td> <td>Length per reel</td> </tr> </table> | | | 09 18 050 7004 | 100 m (328 feet) | 09 18 050 7001 | 30,48 m (100 feet) | Part number | Length per reel | | | | | | | | | |
| 09 18 050 7004 | 100 m (328 feet) | | | | | | | | | | | | | | | | |
| 09 18 050 7001 | 30,48 m (100 feet) | | | | | | | | | | | | | | | | |
| Part number | Length per reel | | | | | | | | | | | | | | | | |