



Specification:
 1. Electrical Char
 Insulation Resistance: 500MΩ min. 500V DC for 1 minute
 Contact Resistance: 30mΩ max.
 Rating Current: 1.5A max.
 Rating Voltage: 150V AC
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

2. Physical Char
 Housing: PBT Glass filled (UL 94V-0) Color: Black
 Soldering Temperature: 235°C for 5 sec.
 Spring Wire: 0.35mm Dia Phosphor Bronze
 6u" Gold plating over Nickel
 Temperature Range: -40°C to +85°C
 Durability: 750 mating cycles min.

3. Packing: Tray

RoHS compliant
 Unit:mm

Scale	Free
TOLERANCE	
.XX	±0.20
.XXX	±0.13
.XXXX	±0.05
DIM	TOL
Angle	+0°30'

Id.	Modification	Date	Name
①	Drawn	04.08.2016	Winnie

Date	Name
04.08.2016	Winnie
04.08.2016	Winnie

Customer-No.	ASSMANN WSW-No.	Drawing-No.	Replace	SHEET
	A-2004-1-4-N-R	ASS 7321 CO		rev00



1 2 3 4 5 6 7

H G F E D C B A