

## Housing - HC-D 50-TFQ-76/O1STM32S - 1645286


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON sleeve housing D50, for double locking latch, height 76 mm, without support 1x M32, lateral conductor exit



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 913144
Weight per Piece (excluding packing)	264.1 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	76 mm
Width	56 mm
Length	82 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HC-D25, A16/A32
Size	D50
Housing type	Sleeve housing
Locking type	For double locking latch
No. of cable outlets	1

# Housing - HC-D 50-TFQ-76/O1STM32S - 1645286

## Technical data

### General

Cable exit	Lateral
Screw connection	none
Type of the screw connection	1x M32
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Approvals

### Approvals

---

Approvals

EAC / GL

---

# Housing - HC-D 50-TFQ-76/O1STM32S - 1645286

## Approvals

Ex Approvals

---

Approvals submitted

---


Approval details

EAC

GL

## Drawings

Dimensional drawing



Dimensional drawing