



**NOTES:**

- METALSHELLS: STEEL; 315µin-470µin ZINC; YELLOW CHROMATE
- INSULATORS: PBT GF UL 94 V-0; BLACK
- CONTACTS: COPPER ALLOY; PLATING: (SEE PART NO.):
  - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
  - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
  - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
- THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
- CONNECTOR IS PART MARKED: **162□10419X CONEC ABC** (see note 3)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		scale: 2:1 (5:1)
				dim. in mm		material: SEE NOTES
				date	name	title: <b>D-SUB FEMALE</b> 9pos. WIRE WRAP with threaded insert
				drawn 26.03.13	Lehmenkühler	
				appd. 27.03.13	Fischer	
				norm		
				d-old		dwg no: Inventor 10
a	Original		<b>CONEC</b> <sup>®</sup>		16K1A3213	sh: 1
rev.	description	date			name	part no: 162□10419X (see note 3)