

Snap-On Connector Interface Adapters

APPLICATIONS:

Tempo's precision Snap-On Connector (SOC) adapters ensure maximum accuracy and repeatability when performing critical measurements on fiber optic systems. Machined from the highest quality materials available, SOC adapters are standard equipment on all Tempo optical power meters, and those of other manufacturers.

A comprehensive range of SOC adapters is available for all industry standard fiber optic connectors and many less common types.



FEATURES

- Single-mode and multimode compatible
- High quality and tight tolerances ensure measurement accuracy and repeatability
- Available for all industry standard connectors and other less common types
- Push-on/pull-off design
- Easy to clean and use
- Compatible with both physical contact (PC) and 8° angled physical contact (APC) interfaces

Snap-On Connector Interface Adapters

SOC SELECTION TABLE

| Connector Type | For all PC Polish (0°) and APC Polish (8°) applications |
|--|--|
| Blank | 1001 |
| D4 | 1089 |
| DIN 47256 | 1010 |
| Diamond HMS-0 (3.5mm) | 1050 |
| Diamond HMS-10A (SMA 2.5) | 1086 |
| E2000 | 10E2 |
| FC | 1020 |
| HP HMS-10 (2.5mm) | 1040 |
| H-P Versalink/Spectran V/Z-pin | 10ZP |
| LC | 10LC |
| MIL-T-29504 Optical Termini | 1038 |
| Mini-BNC | 1047 |
| MT-RJ duplex fiber | 13A2 |
| MT-RJ ferrule | 13AF |
| MU | 10MU |
| POF, MOST | 10M1 |
| Radiall EC | 10E0 |
| Radiall VFO | 1081 |
| SC | 1062 |
| Simplex TOSLINK/Spectran J-pin | 10TB |
| SMA 905/906 | 1087 |
| ST | 1030 |
| Stratos 430/Holtek 38000 | 1057 |
| TR/TX set, duplex TOSLINK/Spectran J-pin | 10TD (10TR and 10TX) |
| Universal 1.25mm* *** | 1026 |
| Universal 2.5mm* ** | 1025 |

ORDERING INFORMATION

| Part No. | Description |
|----------|-------------------------------------|
| 1001 | Blank |
| 1010 | DIN 47256 and AVIM/AVIO |
| 1020 | NTT/FC (All key widths) |
| 1025 | "Quick Connect" (2.5mm ferrule) |
| 1026 | "Quick Connect" (1.25mm ferrule) |
| 1030 | AT&T/ST-PC |
| 1038 | MIL-T-29504 Optical Termini |
| 1040 | HMS-10 (2.5mm) |
| 1047 | Mini-BNC |
| 1050 | Diamond HMS-0 (3.5mm) |
| 1057 | Stratos 430/Holtek 38000 |
| 1062 | NTT/SC-PC |
| 1081 | Radiall VFO |
| 1086 | Diamond HMS-10A (SMA-2.5mm) |
| 1087 | SMA-905/906 |
| 1089 | D4 |
| 10E0 | Radiall |
| 10E2 | Diamond E-2000 |
| 10LC | LC |
| 10M1 | POF, MOST |
| 10MU | MU |
| 10TB | Simplex TOSLINK/Spectran J-pin |
| 10TD | Duplex TOSLINK TR/TX set |
| 10TR | Duplex TOSLINK TX Adapter |
| 10TX | Duplex TOSLINK TR Adapter |
| 10ZP | H-P Versatile Link/Spectran V/Z-pin |
| 13A2 | MT-RJ |
| 13AF | MT-RJ ferrule only |

