



**NOTES:**

**MATERIAL**

- ⑤ 1. Insulator Material: PA9T+30%GF(UL94V-0), Black
  - 2. Contact Material : Brass
  - 3. Contact Plating : Gold flash Over 50µ"Ni
- ELECTRICAL**
- 1. Current Rating : 1.5AMP
  - 2. Withstand Voltage : 500V AC/DC
  - 3. Contact Resistance : 20mΩ max
  - 4. Insulation Resistance: 1000MΩ min
- ENVIRONMENTAL**
- 1. Operation Temperature: -40°C to +105°C
  - ④ 2. Packing: Tube

**Order Information :**

xx: 06,08,10,14,16,20,24,26,30,34,40,44,50,60

**RoHS compliant**  
  
 File No.: E198287 ③

Scale	Free												
<b>TOLERANCE</b>													
X.X	±0.40	⑤	Change the material to PA9T	22.03.2016	Winnie	Drawn	25.01.2006	Alex	Customer-No.	ASSMANN WSW-No.	AWHW2 XXG-0202		
X.XX	±0.25	④	Update the packing	24.02.2014	Amy	Approved	22.03.2016	Winnie					
X.XXX	±0.15	③	Add UL-File No	12.12.2013	Winnie								
Angle°	±3°	②	Update	29.06.2009	Dean				Drawing-No.				
		①	Drawn	25.01.2006	Alex				ASS 2317 CO	Replace	rev05		
			Id.			Modification							



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	A
H	G	F	E	D	C	B	A