



PART NUMBER	ENGINEERING NO.	LENGTH
1300070022	206000A01F030	3' 0" +1.75 - 0 [.9M +44.5 - 0]
1300070024	206000A01F060	6' 0" +2.19 - 0 [1.8M +55.6 - 0]
1300070026	206000A01F120	12' 0" +3.50 - 0 [3.7M +88.9 - 0]
1300070028	206000A01F200	20' 0" +6.50 - 0 [6.1M +165.1 - 0]
1300070030	206000A01F250	25' 0" +12.50 - 0 [7.6M +317.5 - 0]
1300070031	206000A01F300	30' 0" +12.50 - 0 [9.1M +317.5 - 0]
1300070033	206000A01F350	35' 0" +12.50 - 0 [10.7M +317.5 - 0]
1300070035	206000A01F450	45' 0" +12.50 - 0 [13.7M +317.5 - 0]
1300070036	206000A01F500	50' 0" +24.50 - 0 [15.2M +622.3 - 0]
1300070038	206000A01F600	60' 0" +24.50 - 0 [18.2M +622.3 - 0]
1300070039	206000A01F750	75' 0" +24.50 - 0 [22.9M +622.3 - 0]

- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. CABLE ASSEMBLIES ARE BAGGED SEPARATELY IN POLY BAGS WITH BARCODE LABEL ATTACHED TO OUTSIDE OF BAG
 4. WRAP LABEL IS MARKED WITH P/N, DATE CODE VOLTAGE & AMPERAGE
 5. MATES WITH: MINI CHANGE, C-SIZE 6 POLE RECEPTACLE
 6. ELECTRICAL SPECIFICATIONS:
VOLTAGE RATING: 600V
CURRENT RATING: 8 AMPS
 7. ASSEMBLY IS RoHS COMPLIANT

S2	
1	ORANGE
2	BLUE
3	BLACK
4	WHITE
5	RED
6	GREEN YELLOW

WIRING DIAGRAM

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
8	1	LABEL	PLASTIC FILM	BLACK/YELLOW
7	1	OVERMOLD	PVC	YELLOW
6	1	COUPLING NUT	ZINC DIE CAST	BLACK
5	1	FRICITION RING	NYLON	NATURAL
4	6	SOCKET CONTACT	BRASS	GOLD PLATED
3	6	SOCKET SLEEVE	STAINLESS STEEL	
2	1	INSERT, FEMALE, 6 POLE	PVC	YELLOW
1	1	CABLE, 16-6 ST00W/ST	PVC JACKET	YELLOW

RELEASED EC NO: MNA2009-0627 DRAWN BY: DRWINRSTONE 2009/04/03 CHKD BY: WOODMAN APPR: J. MURPHY 2009/04/08	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± .005</td> <td>± .0005</td> </tr> <tr> <td>3 PLACES</td> <td>± .005</td> <td>± .0005</td> </tr> <tr> <td>2 PLACES</td> <td>± .010</td> <td>± .001</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.3</td> <td>± .012</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	± .005	± .0005	3 PLACES	± .005	± .0005	2 PLACES	± .010	± .001	1 PLACE	± 0.3	± .012	DIMENSION STYLE IN/MM	SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
			mm	INCH																	
4 PLACES	± .005	± .0005																			
3 PLACES	± .005	± .0005																			
2 PLACES	± .010	± .001																			
1 PLACE	± 0.3	± .012																			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE CHART	DRAWN BY: R. STONE 2009/04/02 CHECKED BY: B. WOODMAN 2009/04/03 APPROVED BY: J. MURPHY 2008/04/06	TITLE MINI-CHANGE CORD ASSY FEMALE, B-SIZE 6 POLE	MOLEX INCORPORATED	DOCUMENT NO. SD-130007-001	SHEET NO. 1 OF 1															

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION