

# PANDUIT® Stainless Steel Strapping

## Stainless Steel Strapping



### REPLACES TRADITIONAL WING SEAL STRAPS

- Suited to applications requiring higher loop tensile strength and/or wider bearing surfaces than **PAN-STEEL™** ties
- Fast and easy to install using **PANDUIT** installation tool
- Safe to handle—no sharp edges

## STRAPPING Standard Sizes



- Suited to applications requiring higher loop tensile strength and/or wider bearing surfaces than **PAN-STEEL** ties
- Fast and easy to install using **PANDUIT** installation tool.
- Safe to handle—no sharp edges
- Buckle design provides low finished profile—after tensioning, cut end is locked inside buckle
- Standard material is 304 stainless, non-magnetic

\*Nylon coated straps available. Contact factory.

| <b>PANDUIT®</b><br>Part No.              | Max. Bundle<br>Dia.<br>In. (mm) | Approx.<br>Length<br>In. (mm) | Approx.<br>Width<br>In. (mm) | Min. Loop<br>Tensile<br>Strength<br>lbs. (n) | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. |
|--|---------------------------------|-------------------------------|------------------------------|--|----------------------|----------------------|
| <b>304 STAINLESS STEEL - .015" THICK</b> |                                 |                               |                              |  |                      |                      |
| MS2X375X15-LS                            | 2.00 (50)                       | 10.5 (266)                    | .375<br>(10)                 | 300<br>(1335)                                | 50                   | 250                  |
| MS4X375X15-LS                            | 4.00 (102)                      | 16.2 (412)                    |                              |  | 50                   | 250                  |
| MS6X375X15-LS                            | 6.00 (152)                      | 22.5 (572)                    |                              |  | 50                   | 250                  |
| MS8X375X15-LS                            | 8.00 (203)                      | 28.7 (729)                    |                              |  | 50                   | 250                  |
| MS10X375X15-LS                           | 10.00 (254)                     | 35.0 (889)                    |                              |  | 50                   | 250                  |
| <b>304 STAINLESS STEEL - .020" THICK</b> |                                 |                               |                              |  |                      |                      |
| MS4X500X15-LS                            | 4.00 (102)                      | 16.2 (412)                    | .500<br>(12)                 | 500<br>(2224)                                | 50                   | 250                  |
| MS6X500X15-LS                            | 6.00 (152)                      | 22.5 (572)                    |                              |  | 50                   | 250                  |
| MS8X500X15-LS                            | 8.00 (203)                      | 28.7 (729)                    |                              |  | 50                   | 250                  |
| MS10X500X15-LS                           | 10.00 (254)                     | 35.0 (889)                    |                              |  | 50                   | 250                  |
| MS4X625X15-LS                            | 4.00 (102)                      | 16.2 (412)                    | .625<br>(16)                 | 600<br>(2670)                                | 50                   | 250                  |
| MS6X625X15-LS                            | 6.00 (152)                      | 22.5 (572)                    |                              |  | 50                   | 250                  |
| MS8X625X15-LS                            | 8.00 (203)                      | 28.7 (729)                    |                              |  | 50                   | 250                  |
| MS10X625X15-LS                           | 10.00 (254)                     | 35.0 (889)                    |                              |  | 50                   | 250                  |
| <b>304 STAINLESS STEEL - .020" THICK</b> |                                 |                               |                              |  |                      |                      |
| MS4X500X20-LS                            | 4.00 (102)                      | 16.2 (412)                    | .500<br>(12)                 | 500<br>(2224)                                | 50                   | 250                  |
| MS6X500X20-LS                            | 6.00 (152)                      | 22.5 (572)                    |                              |  | 50                   | 250                  |
| MS8X500X20-LS                            | 8.00 (203)                      | 28.7 (729)                    |                              |  | 50                   | 250                  |
| MS10X500X20-LS                           | 10.00 (254)                     | 35.0 (889)                    |                              |  | 50                   | 250                  |

## Custom Length Strapping System



- Provides job-site versatility with minimum inventory
- Gives custom capability on larger diameters
- 304 stainless steel
- Buckle is easy to install—just slip onto strapping and turn strapping back on bundle

| <b>PANDUIT®</b><br>Part No. | Thickness<br>In. (mm)           | Approx.<br>Width<br>In. (mm) | Used<br>With<br>Buckle | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. |
|-----------------------------|---------------------------------|------------------------------|------------------------|----------------------|----------------------|
| <b>STRAPPING</b>            |                                 |                              |                        |                      |                      |
| MS375X15-TSR                | .015 (0.4)                      | .375 (10)                    | MSB375                 | 200*                 | —                    |
| MS500X15-TSR                | .015 (0.4)                      | .500 (12)                    | MSB500                 | 200*                 | —                    |
| MS500X20-TSR                | .020 (0.5)                      | .500 (12)                    | MSB500                 | 200*                 | —                    |
| MS625X15-TSR                | .015 (0.4)                      | .625 (16)                    | MSB625                 | 200*                 | —                    |
| <b>BUCKLE</b>               |                                 |                              |                        |                      |                      |
| MSB375-CS                   | Used with .375" width strapping |                              |                        | 100                  | 1000                 |
| MSB500-CS                   | Used with .500" width strapping |                              |                        | 100                  | 1000                 |
| MSB625-CS                   | Used with .625" width strapping |                              |                        | 100                  | 1000                 |

\*Standard Package - TSR = 200 ft. reel. Order the number of reels required. Order the number of bundles required, in multiples of std. pkg. qty.

## INSTALLATION TOOL



BT2MS75

- Replacement nose and gripper provide an economical means to keep tool operating efficiently in the future

| <b>PANDUIT®</b><br>Part No. | Description   | Pkg.<br>Qty. |
|-----------------------------|---|--------------|
| BT2MS75                     | Tensions, cuts strapping and secures the buckle tab. Used with all widths and thicknesses of <b>PANDUIT</b> strapping | 1            |
| BT2N75                      | Replacement nose section for BT2MS75 tool   | 1            |
| KT2MG                       | Replacement tension gripper for BT2MS75 tool  | 1            |