


LOC		DIST		REVISIONS			
AD	39	P	LTR	DESCRIPTION	DATE	DMN	APVD
		0		RELEASED	11-NOV-96	EB	GD

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
- FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, OVER 0.00127 [.000050] NICKEL, ENTIRE POST.



RECOMMENDED HOLE LAYOUT

LOC	DIST	NO. OF POSITIONS	PART NUMBER
101.19	99.06	39	4-146504-0
[3.984]	[3.900]		
98.65	96.52	38	3-146504-9
[3.884]	[3.800]		
96.11	93.98	37	3-146504-8
[3.784]	[3.700]		
93.57	91.44	36	3-146504-7
[3.684]	[3.600]		
91.03	88.90	35	3-146504-6
[3.584]	[3.500]		
88.49	86.36	34	3-146504-5
[3.484]	[3.400]		
85.95	83.82	33	3-146504-4
[3.384]	[3.300]		
83.41	81.28	32	3-146504-3
[3.284]	[3.200]		
80.87	78.74	31	3-146504-2
[3.184]	[3.100]		
78.33	76.20	30	3-146504-1
[3.084]	[3.000]		
75.79	73.66	29	3-146504-0
[2.984]	[2.900]		
73.25	71.12	28	2-146504-9
[2.884]	[2.800]		
70.71	68.58	27	2-146504-8
[2.784]	[2.700]		
68.17	66.04	26	2-146504-7
[2.684]	[2.600]		
65.63	63.50	25	2-146504-6
[2.584]	[2.500]		
63.09	60.96	24	2-146504-5
[2.484]	[2.400]		
60.55	58.42	23	2-146504-4
[2.384]	[2.300]		
58.01	55.88	22	2-146504-3
[2.284]	[2.200]		
55.47	53.34	21	2-146504-2
[2.184]	[2.100]		
52.93	50.80	20	2-146504-1
[2.084]	[2.000]		
50.39	48.26	19	2-146504-0
[1.984]	[1.900]		
47.85	45.72	18	1-146504-9
[1.884]	[1.800]		
45.31	43.18	17	1-146504-8
[1.784]	[1.700]		
42.77	40.64	16	1-146504-7
[1.684]	[1.600]		
40.23	38.10	15	1-146504-6
[1.584]	[1.500]		
37.69	35.56	14	1-146504-5
[1.484]	[1.400]		
35.15	33.02	13	1-146504-4
[1.384]	[1.300]		
32.61	30.48	12	1-146504-3
[1.284]	[1.200]		
30.07	27.94	11	1-146504-2
[1.184]	[1.100]		
27.53	25.40	10	1-146504-1
[1.084]	[1.000]		
24.99	22.86	9	1-146504-0
[.984]	[.900]		
22.45	20.32	8	146504-9
[.884]	[.800]		
19.91	17.78	7	146504-8
[.784]	[.700]		
17.37	15.24	6	146504-7
[.684]	[.600]		
14.83	12.70	5	146504-6
[.584]	[.500]		
12.29	10.16	4	146504-5
[.484]	[.400]		
9.75	7.62	3	146504-4
[.384]	[.300]		
7.21	5.08	2	146504-3
[.284]	[.200]		
4.67	2.54	1	146504-2
[.184]	[.100]		
2.13	-	-	146504-1
[.084]	-	-	
G	F	E	

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP TECHNOLOGIES. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING DEPARTMENT SHALL BE CONTACTED FOR THE LATEST REVISION.

DIMENSIONS: mm (INCH)	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±.01 1 PLC ±.01 2 PLC ±.01 3 PLC ±.01 4 PLC ±.01 ANGLES ±	DMN E. BRANDBERG CHK G. DUBNICZKI AMP/D G. DUBNICZKI PRODUCT SPEC APPLICATION SPEC WEIGHT CUSTOMER DRAWING	11-NOV-96 11-NOV-96 11-NOV-96 11-NOV-96	AMP Incorporated Harrisburg, PA 17105-3508
MATERIAL	FINISH	NO. OF POSITIONS	PART NUMBER	NAME HEADER ASSEMBLY, MOD 11, STACKING, DOUBLE ROW, .025 SQ. POST, UNSHROUDED
		A1	00779	SCALE 4:1 SHEET 1 OF 1 REV 0