



RECOMMENDED LAYOUT

- ▲ NYLON, UL 94-VO RATED, RED.
- ▲ PHOSPHOR BRONZE.
- ▲ 3.81um [.000150] MIN TIN-LEAD OVER 1.27um [.000050] MIN NICKEL.
- ▲ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 4.95 [.195] MIN FROM MATING END 3.81um [.000150] MIN TIN-LEAD FOR A LENGTH OF 4.88 [.192] MIN ON OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.
- ▲ 3.81um [.000150] MIN TIN OVER 1.27um [.000050] MIN NICKEL.
- ▲ 0.76um [.000030] MIN GOLD FOR A LENGTH OF 4.95 [.195] MIN FROM MATING END 3.81um [.000150] MIN TIN FOR A LENGTH OF 4.88 [.192] MIN ON OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.

4.60 [.181]	▲6	NO	1-207532-1
4.60 [.181]	▲6	YES	1-207532-0
4.60 [.181]	▲6	NO	207532-9
4.60 [.181]	▲5	YES	207532-8
9.68 [.381]	▲3	NO	207532-7
4.60 [.181]	▲4	NO	207532-4
4.60 [.181]	▲4	YES	207532-3
4.60 [.181]	▲3	NO	207532-2
4.60 [.181]	▲3	YES	207532-1
A		CONTACT FINISH	MOUNTING TABS
		PART NO	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN L/SIPE 03/19/92	APVD R. STONE 3-25-92	TYCO Electronics Tyco Electronics Corporation Harrisburg, Pa 17105-3608
0 PLC ± -	1 PLC ± -	2 PLC ± 0.25 [.010]	3 PLC ± -	4 PLC ± -
MATERIAL HOUSING: 1		FINISH CONTACT: SEE TABLE		NAME A. TRAVIS 3-25-92
CUSTOMER DRAWING		SIZE A1	SCALE 4:1	RESTRICTED TO

SOCKET HEADER ASSEMBLY, 24 POSITION, METRIMATE
 108-10033
 00779 ©=207532