

Features

Regulated Converters

- 4:1 Wide Input Voltage Range
- 1.6kVDC Isolation
- UL, IEC/EN Certified & EN50155 Pending
- Efficiency up to 89%
- OVP, OCP & OTP
- +105°C max Case Temperature

RECOM
DC/DC Converter

RPA30-AW

30 Watt

1" x 1"



**Single & Dual
Output**



c **UL** **US**
E224736

**UL60950-1 Certified
IEC/EN60950 Certified
EN50155 Pending**


Selection Guide

Part Number	Input Voltage Range [VDC]	Output Voltage [VDC]	Output Current [mA]	Input ⁽¹⁾ Current [mA]	Efficiency ⁽¹⁾ typ. [%]	Max. Capacitive Load [μF]
RPA30-243.3SAW ^(2,3)	9-36	3.3	7500	1172	88	10000
RPA30-2405SAW ^(2,3)	9-36	5	6000	1404	89	10000
RPA30-2412SAW ^(2,3)	9-36	12	2500	1420	88	1000
RPA30-2415SAW ^(2,3)	9-36	15	2000	1420	88	1000
RPA30-2412DAW ^(2,3)	9-36	±12	±1250	1420	88	±1000
RPA30-2415DAW ^(2,3)	9-36	±15	±1000	1420	88	±680

Notes:

Note1: Tested at nominal Vin, full load and at +25°C ambient

Model Numbering



Ordering Examples

RPA30-243.3SAW = 24V Input, 3.3V Output, Single, no CTRL pin

RPA30-2405SAW/P = 24V Input, 5V Output, Single, Pos. CTRL function

RPA30-2415SAW-HC = 24V Input, 15V Output, Single, no CTRL pin, glued Heat-sink

RPA30-2415DAW/N-HC = 24V Input, 15V Output, Dual, Neg. CTRL function, glued Heat-sink





Notes:

Note2: part without suffixes is without CTRL pin, trim pin fitted
add suffix "P" for positive CTRL function (1=ON, 0=OFF), trim pin fitted
add suffix "N" for negative CTRL function (0=ON, 1=OFF), trim pin fitted
trim pin is only available for single outputs

Note3: add suffix "-HC" for glued Heat-sink (compatible with all other suffixes)

Specifications measured @ $ta = 25^\circ\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

BASIC CHARACTERISTICS				
Parameter	Condition	Min.	Typ.	Max.
Internal Input Filter				Pi-Type
Input Voltage Range		9VDC	24VDC	36VDC
Input Surge Voltage	100ms max.			50VDC
Quiescent Current				
Start-up time	Power up CTRL ON/OFF		8ms	16ms
Internal Operating Frequency			550kHz	
Minimum Load		0%		
Ripple and Noise	20MHz BW, 10µF tantalum capacitor and 1µF ceramic capacitor		50mVp-p	
Under Voltage Lockout (UVLO)	DC-DC ON DC-DC OFF	8VDC 7VDC	8.5VDC 7.5VDC	9VDC 8VDC
ON/OFF Control	Positive Logic	DC-DC ON DC-DC OFF		Open or $2.4 < V_r < 10\text{VDC}$ Short or $0 < V_r < 0.8\text{VDC}$
	Negative Logic	DC-DC ON DC-DC OFF		Short or $0 < V_r < 0.8\text{VDC}$ Open or $2.4 < V_r < 10\text{VDC}$
Input current of CTRL pin			6mA	
Output Voltage Trimming	Single Outputs	-10%		+10%


RPA30-243.3SAW
Efficiency vs. Output Current

Power Dissipation vs Output Current

RPA30-2405SAW
Efficiency vs. Output Current

Power Dissipation vs Output Current


continued on next page


Specifications measured @ $T_a = 25^\circ\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

RPA30-2412SAW

Efficiency vs. Output Current




Power Dissipation vs Output Current




RPA30-2415SAW

Efficiency vs. Output Current




Power Dissipation vs Output Current




RPA30-2412DAW

Efficiency vs. Output Current



Power Dissipation vs Output Current




continued on next page


Specifications measured @ $ta = 25^\circ\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

RPA30-2415DAW

Efficiency vs. Output Current




Power Dissipation vs Output Current



OUTPUT TRIM

Output Voltage Trimming

RPA30-AW converters offer the feature of trimming the output voltage over a certain range around the nominal value by using external trim resistors. The values for trim resistors shown in trim tables below are according to standard E96 values; therefore, the specified voltage may slightly vary.



RPA30-243.3SAW

Trim up	1	2	3	4	5	6	7	8	9	10	%
Vout =	3.33	3.36	3.39	3.43	3.46	3.49	3.53	3.56	3.59	3.63	Volts
R _U =	402	169	100	75	47.5	34.8	26.1	17.8	12.1	8.06	kOhms
Trim down	1	2	3	4	5	6	7	8	9	10	%
Vout =	3.27	3.23	3.20	3.17	3.14	3.10	3.07	3.04	3.0	2.97	Volts
R _D =	402	191	113	75	52.3	39.2	26.7	20	12.1	8.06	kOhms

RPA30-2405SAW

Trim up	1	2	3	4	5	6	7	8	9	10	%
Vout =	5.05	5.10	5.15	5.20	5.25	5.30	5.35	5.40	5.45	5.50	Volts
R _U =	604	243	147	95.3	68.1	39.2	34.8	22.1	15	8.06	kOhms
Trim down	1	2	3	4	5	6	7	8	9	10	%
Vout =	4.95	4.90	4.85	4.80	4.75	4.70	4.65	4.60	4.55	4.50	Volts
R _D =	604	287	169	124	105	78.7	54.9	39.2	15	0.5	kOhms

RPA30-2412SAW

Trim up	1	2	3	4	5	6	7	8	9	10	%
Vout =	12.12	12.24	12.36	12.48	12.6	12.72	12.84	12.96	13.08	13.20	Volts
R _U =	604	267	162	105	75	499	40.2	24.9	18.2	10	kOhms
Trim down	1	2	3	4	5	6	7	8	9	10	%
Vout =	11.88	11.76	11.64	11.52	11.40	11.28	11.16	11.04	10.92	10.80	Volts
R _D =	750	309	200	124	90.9	64.9	45.3	32.4	20	12.1	kOhms

continued on next page

Specifications measured @ $T_a = 25^\circ\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

RPA30-2415SAW											
Trim up	1	2	3	4	5	6	7	8	9	10	%
$V_{out} =$	15.15	15.30	15.45	15.60	15.75	15.90	16.05	16.20	16.35	16.50	Volts
$R_u =$	1000	243	200	130	90.9	61.9	40.2	30.1	24.9	10	kOhms
Trim down	1	2	3	4	5	6	7	8	9	10	%
$V_{out} =$	14.85	14.70	14.55	14.40	14.25	14.10	13.95	13.80	13.65	13.50	Volts
$R_d =$	1000	348	210	140	95.3	68.1	45.3	30.1	18.2	8.06	kOhms

REGULATION		
Parameter	Condition	Value
Output Accuracy	Single & Dual	$\pm 2.0\%$ max.
Line Regulation	low line to high line	$\pm 0.2\%$ max. $\pm 0.5\%$ max.
Load Regulation	3.3V out 5V out 12V out , 15V out $\pm 12V_{out}$, $\pm 15V_{out}$	$\pm 0.3\%$ $\pm 0.2\%$ $\pm 0.1\%$ $\pm 1.0\%$
Cross Regulation	asymmetrical 25%<>100% load	$\pm 3.0\%$ max.
Transient Response	50-75%, full load, 0.1A/ μ s 25% load step change	$\pm 3.0\%$ V_{out} typ. 250 μ s typ.

PROTECTION			
Parameter	Condition	Value	
Short Circuit Protection (SCP)	below 100m Ω	continuous, auto recovery	
Over Voltage Protection (OVP)		115%-150% Output Voltage, Hiccup, auto recovery	
Over Current Protection (OCP)		110%-160% Output Current, Hiccup	
Over Temperature Protection (OTP)		+115°C $\pm 5^\circ\text{C}$	
Isolation Voltage ⁽⁵⁾	I/P to O/P	tested for 1 minute	1.6kVDC
Isolation Resistance			10M Ω min.
Isolation Capacitance			1100pF typ.
Insulation Grade			basic
Notes:			
Note4: An input fuse is required if the mains supply is not over-current protected. Recommended fuse: 4A slow blow type.			
Note5: For repeat Hi-Pot testing, reduce the time and/or the test voltage.			

ENVIRONMENTAL		
Parameter	Condition	Value
Operating Temperature Range ⁽⁶⁾		-40°C to [refer to thermal calculation]
Maximum Case Temperature		+105°C
Temperature Coefficient		0.02%/°C
Thermal Impedance		please refer to table 1
Operating Altitude		2000m
Operating Humidity		95% RH
MTBF		5888 x 10 ³ hours

continued on next page

Specifications measured @ $T_a = 25^\circ\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

Table 1: Thermal Impedance

airflow [m/s]	without Heatsink		with Heatsink	
	R _{th} without PCB [°C/W]	R _{th} with PCB ⁽⁶⁾ [°C/W]	R _{th} without PCB [°C/W]	R _{th} with PCB ⁽⁶⁾ [°C/W]
0.1	17.8	12.5	16.0	11.3
0.2	16.0	11.2	14.4	10.1
0.5	14.0	9.7	12.6	8.7
1.0	10.0	7.1	9.0	6.4
1.5	8.3	5.8	7.5	5.2
2.0	6.3	4.4	5.7	4.0

Notes:

Note6: Test PCB:160x100mm105μm (Eurocard), double layer

Thermal Calculation

choose your model:

RPA30-2405SAW (with PCB⁽⁶⁾)

- Load conditions in application (e.g. 50%)
- Airflow conditions in application (e.g. 0.5m/s)
- use R_{th} from Table1 (9.7°C/W)

Calculation:

$$\begin{aligned} I_{out} &= 50\% \\ R_{th} &= 9.7^\circ\text{C}/\text{W} \\ P_{DISS} &= 2.2\text{W} \\ T_{CASEmax} &= 105^\circ\text{C} \end{aligned}$$

$$T_{OVER} = R_{th} \times P_{Dis} = 9.7^\circ\text{C}/\text{W} \times 2.2\text{W} = 21.3^\circ\text{C}$$

$$T_{AMBmax} = T_{CASEmax} - T_{OVER} = 105^\circ\text{C} - 21.3^\circ\text{C} = 83.7^\circ\text{C}$$

choose your model:

RPA30-2405SAW-HC (with PCB⁽⁶⁾)

- Load conditions in application (e.g. 50%)
- Airflow conditions in application (e.g. 0.5m/s)
- use R_{th} from Table1 (8.7°C/W)


Calculation:

$$\begin{aligned} I_{out} &= 50\% \\ R_{th} &= 8.7^\circ\text{C}/\text{W} \\ P_{DISS} &= 2.2\text{W} \\ T_{CASEmax} &= 105^\circ\text{C} \end{aligned}$$


$$T_{OVER} = R_{th} \times P_{Dis} = 8.7^\circ\text{C}/\text{W} \times 2.2\text{W} = 19.1^\circ\text{C}$$

$$T_{AMBmax} = T_{CASEmax} - T_{OVER} = 105^\circ\text{C} - 19.1^\circ\text{C} = 85.9^\circ\text{C}$$

RPA30-2405SAW



RPA30-2405SAW-HC



SAFETY AND CERTIFICATIONS


Certificate Type (Safety)	Report / File Number	Standard
Information Technology Equipment, General Requirements for Safety	E224736-A39 + A40	UL60950-1, 2nd Edition, 2014 CSA C22.2 No. 60950, 2nd Edition, 2014
IEC/EN Information Technology Equipment - General Requirements for Safety (CB Scheme)	E224736-A39-CB + A40-CB	IEC60950-1, 2nd Edition, 2005 + AM2, 2013 EN60950-1, 1st Edition, 2006 + AM2, 2013
EN Information Technology Equipment - General Requirements for Safety (LVD Directive)		EN60950-1, 1st Edition, 2006
Railway Applications - Electrical Equipment used on rolling stock	pending	EN50155, 1st Edition, 2007

continued on next page

Specifications measured @ $T_a = 25^\circ\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

EMC Compliance (designed to meet)	Condition	Standard / Criterion
Information technology equipment - Radio disturbance characteristics Limits and methods of measurement	with external filter	EN55022, Class A, 2010

EMI Filtering according to EN50121-3-2 and EN55022 Class A



C1	L1
47µF/50V electrolytic capacitor	1µH Choke


Notes:

Note7: Diode is only needed for EN50155.

DIMENSIONS and PHYSICAL CHARACTERISTICS

Parameter	Type	Value
Material	Case Baseplate Potting	Al Alloy, anodize black non-conductive FR4 Silicone
Package Dimensions (LxWxH)	without Heat-sink with Heat-sink	25.4 x 25.4 x 10.2mm 25.4 x 25.4 x 16.8mm
Package Weight	without Heat-sink with Heat-sink	17g typ. 21g typ.

Dimension Drawing (mm)



Pin Connections




Pin #	Single	Dual
1	+Vin	+Vin
2	-Vin	-Vin
3	CTRL ⁽²⁾	CTRL ⁽²⁾
4	-Vout	-Vout
5	Trim	Com
6	+Vout	+Vout

Pin Pitch Tolerance $\pm 0.25\text{mm}$
Pin dimension tolerance $\pm 0.1\text{mm}$
 $XX.X \pm 0.5\text{mm}$
 $XX.XX \pm 0.25\text{mm}$

continued next page

Specifications measured @ $ta = 25^{\circ}\text{C}$, resistive load, nominal V_{in} and rated I_{out} unless otherwise noted

Heat-sink Dimension Drawing (mm)



PACKAGING INFORMATION

Parameter	Type		Value
Packaging Dimensions (LxWxH)	without Heat-sink		285.0 x 27.6 x 19.0mm
	with Heat-sink	tube	285.0 x 27.6 x 25.8mm
Packaging Quantity			10pcs
Storage Temperature Range			-55°C to +125°C
Storage Humidity			5% - 95% RH

The product information and specifications are subject to change without prior notice. RECOM products are not authorized for use in safety-critical applications (such as life support) without RECOM's explicit written consent. A safety-critical application is defined as an application where a failure of a RECOM product may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The buyer shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.