




THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
CM	0	N		REVISED PER ECO-12-007612	03AUG12	KH SM	



- 1 MATERIAL:
CONNECTOR - NYLON UL94V-2.
CONTACTS - 0.30[.012] THICK COPPER ALLOY.
PLATING - 0.00038[.000015] GOLD THK OR 0.00008[.000003] MIN THK GOLD FLASH OVER 0.00030[.000012] THK PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, IN CONTACT AREA.
0.00203[.000080] MIN THICKNESS BRIGHT TIN-LEAD IN SLOT AREA FOR 641175-2 THRU 2-641175-4 OR MATTE WHISKER MITIGATED TIN IN SLOT AREA FOR 3-641175-2 THRU 5-641175-4 OVER NICKEL UNDERPLATE.
- 2 CONTACTS ACCEPT 22 AWG WIRE WITH 2.41[.095] MAX INSULATION DIAMETER.
- 3 CONTACTS MUST ACCEPT 1.14±0.03[.045±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.
- 4 IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.
- 5 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 6 HOUSING FEATURES ARE: FEED-THRU WITHOUT LOCKING RAMP.
- 7 RED COLOR STRIPE ON HOUSING (NOT SHOWN) MAY RUN DOWN BETWEEN RIBS.
- 8 NOTE DELETED.
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

CONTACT FINISH	DIM A	NO. OF CIRCUITS	PART NO.
TIN	95.10 [3.744]	24	5-641175-4
TIN	91.14 [3.588]	23	5-641175-3
TIN	87.17 [3.432]	22	5-641175-2
TIN	83.21 [3.276]	21	5-641175-1
TIN	79.25 [3.120]	20	5-641175-0
TIN	75.29 [2.964]	19	4-641175-9
TIN	71.32 [2.808]	18	4-641175-8
TIN	67.36 [2.652]	17	4-641175-7
TIN	63.40 [2.496]	16	4-641175-6
TIN	59.44 [2.340]	15	4-641175-5
TIN	55.47 [2.184]	14	4-641175-4
TIN	51.51 [2.028]	13	4-641175-3
TIN	47.55 [1.872]	12	4-641175-2
TIN	43.59 [1.716]	11	4-641175-1
TIN	39.62 [1.560]	10	4-641175-0
TIN	35.66 [1.404]	9	3-641175-9
TIN	31.70 [1.248]	8	3-641175-8
TIN	27.74 [1.092]	7	3-641175-7
TIN	23.77 [.936]	6	3-641175-6
TIN	19.81 [.780]	5	3-641175-5
TIN	15.85 [.624]	4	3-641175-4
TIN	11.89 [.468]	3	3-641175-3
TIN	7.92 [.312]	2	3-641175-2
TIN-LEAD	95.10 [3.744]	24	2-641175-4
TIN-LEAD	91.14 [3.588]	23	2-641175-3
TIN-LEAD	87.17 [3.432]	22	2-641175-2
TIN-LEAD	83.21 [3.276]	21	2-641175-1
TIN-LEAD	79.25 [3.120]	20	2-641175-0
TIN-LEAD	75.29 [2.964]	19	1-641175-9
TIN-LEAD	71.32 [2.808]	18	1-641175-8
TIN-LEAD	67.36 [2.652]	17	1-641175-7
TIN-LEAD	63.40 [2.496]	16	1-641175-6
TIN-LEAD	59.44 [2.340]	15	1-641175-5
TIN-LEAD	55.47 [2.184]	14	1-641175-4
TIN-LEAD	51.51 [2.028]	13	1-641175-3
TIN-LEAD	47.55 [1.872]	12	1-641175-2
TIN-LEAD	43.59 [1.716]	11	1-641175-1
TIN-LEAD	39.62 [1.560]	10	1-641175-0
TIN-LEAD	35.66 [1.404]	9	641175-9
TIN-LEAD	31.70 [1.248]	8	641175-8
TIN-LEAD	27.74 [1.092]	7	641175-7
TIN-LEAD	23.77 [.936]	6	641175-6
TIN-LEAD	19.81 [.780]	5	641175-5
TIN-LEAD	15.85 [.624]	4	641175-4
TIN-LEAD	11.89 [.468]	3	641175-3
TIN-LEAD	7.92 [.312]	2	641175-2

SUPERCEDED
9

SUPERCEDED
9

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN B. LEWIS 2-12-91
 CHK R. SWING 2-12-91
 APVD -
 PRODUCT SPEC 108-1051
 APPLICATION SPEC 114-1020
 MATERIAL - 1
 FINISH -

TE Connectivity
 MTA-156 CONNECTOR ASSEMBLY,
 22 AWG, STANDARD

SIZE A2 CAGE CODE 00779 DRAWING NO. C-641175 RESTRICTED TO -
 SCALE 4:1 SHEET 1 OF 1 REV N