

NOTES:

MATERIAL

1. Insulator
Material: PBT+30%GF(UL94V-0), Grey
2. Contact Material : Brass
3. Contact Plating : Sn Over 50μ " Ni

ELECTRICAL


1. Current Rating : 3.0AMP
2. Withstand Voltage : 1000V AC/DC
4. Contact Resistance : 20m Ω max
5. Insulation Resistance: 1000M Ω min

ENVIRONMENTAL

1. Operation Temperature: -40°C to +105°C
2. Packing : Tray

RoHS compliant
Unit: mm



Scale	Free	⑦	Add recommended PCB layout	16.07.2015	Ray		Date	Name	Customer-No.
TOLERANCE		⑥	Add UL file no.	12.12.2013	Amy	Drawn	31.07.2006	Hellwig	ASSMANN WSW-No. AWLP xx/3,2-T
X.X	± 0.40	⑤	Add multiple pin	17.09.2013	Winnie	Approved	16.07.2015	Ray	
X.XX	± 0.25	④	Add 18pin product	06.09.2013	Ray				
X.XXX	± 0.15	③	Update	16.03.2009	Dean				
Angle	$\pm 3^\circ$	②	Redraw	09.03.2009	Dean				Drawing-No. ASS 1197 CO rev07
		Id.	Modification	Date	Name			Replace dd 15.11.01	