

- RC-06S1N12QBEJ - 1593919

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Rear panel feed-through, with Pg9 connection thread, straight, shielded: Yes, Screw locking, M23, Number of positions: 6, Type of contact: Socket, Solder connection, Axial O-ring, Central fixing, Panel thickness max.: 6.5 mm, Cable diameter: 6.5 mm ... 8 mm



Key commercial data

Packing unit	1 pc
Custom tariff number	85366990
Country of origin	Germany

Technical data

Product type	Circular connector (cable-side)
Coding	N
Number of positions	6
Rated voltage (IEC)	300
Rated current (IEC)	20
Signal type	Signal
Connection method	Solder connection

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440103

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121

- RC-06S1N12QBEJ - 1593919

Classifications

ETIM

ETIM 5.0	EC001121
----------	----------

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Drawings

Schematic diagram

