



MIL-DTL 5015 (SAE-AS50151)

MIL-DTL 5015 Connector

With a proven history of engineering and manufacturing excellence spanning over 90 years, ITT has delivered a broad range of innovative product solutions that have and continue to enable our customers to meet their most demanding design requirements. ITT's design centers provide time proven high quality products and exceptional service to customers through a global network of field application engineers, sales force and manufacturing facilities.

The MIL-DTL 5015 (SAE-AS50151) connector series provides a cost effective solution for use in both industrial and military applications. This ITT product line has a 60 year legacy of delivering uncompromising durability and value, and continues to meet today's demanding design requirements for a broad range of customer applications. These connectors utilize robust materials combined with precision manufacturing and stringent quality control to deliver superior performance.

Product Features

- 5 polarizations available
- Rated 500 mating cycles
- Individual wire sealing grommet
- RoHS compliant options available
- Housings available in 4 plating options
- Bonded-In contacts providing 30 PSI sealing
- Available with high power contact sizes from 8 to 0
- Fitted with customized, metric/PG or standard endbell/adaptors



Innovative Interconnect Benefits

- Lower cost options
- Threaded coupling system
- Silver plated contact option
- Polychloroprene insulator material
- State-of-the-art manufacturing facilities providing enhanced customer service and reduced lead time
- Aluminum alloy shells available in a variety of plating options including: OD cadmium, black/green zinc chromate, and RoHS compliant nickel, electroless nickel and black zinc cobalt

Applications

- Machine Tools
- Generators
- Process Equipment
- Test Equipment
- Lighting Equipment
- Traffic Control Signals
- Robotic Devices
- Transportation
- Welding Equipment



MIL-DTL 5015 Selection Guide

Max. Voltage	Max. Current	Operating Temp	Durability
1000-7000 rms	Up to 150 test amps	-55 to +200 degrees C	500 mating cycles

5015 Product Line Talking Dog



Series Prefix	MS-E/F/R/ER (MIL-C-5015)
Designation	MS - Conforms to MIL-C-5015
	CA - ITT Cannon designation
	CAR - RoHS compliant
Shell Style	3100 - Wall mounting receptacles
	3101 - Cable connecting plug
	3102 - Box mounting receptacle
	3106 - Straight plug
	3108 - 90° Angle plug
Class	A - Plastic (unsealed) insulator with solid endbell
	B - Plastic (unsealed) insulator with split endbell
	E - Resilient insulator and integral clamp for cable strain relief
	F - Resilient insulator and integral clamp for cable strain relief with O-ring seal under the coupling nut
	R - Environmental with resilient insulators and shortened light weight endbell
Shell Size	8S, 10S, 12, 12S, 14, 14S, 16S, 16, 18, 20, 22, 24, 28, 32, 36, 40, 44, 48
Contact Type	P - Pin
	S - Socket
Alternate Insert Position	W, X, Y, Z (omit for normal)
Modification Code	A71 - Electroless nickel hardware, RoHS
	A176 - Contacts hard gold over nickel, RoHS
	A206 - Black zinc cobalt hardware, RoHS
	F42 - Connector supplied without endbell, grommet and ferrule
	F80 - Snap-in crimp contacts
	F183 - Snap-in crimp contacts for metric conductors
	DN - CA3106 (plug only), endbell for shrink boot adapter
	A232 - Black zinc cobalt hardware, RoHS European version
	A233 - Green zinc cobalt hardware, European version

When ordering MS3106F to the Cannon part number, designate CA06R.

¹ Modification code is used only when other than power contacts are to be installed (i.e., shielded, thermocouple, etc.)

Visit us online at www.ittcannon.com, or these social media networks:



ITT Corporation

Americas:
Wayde King
714.628.8264
wayde.king@ittcorp.com

Europe:
Bernhard Rupp
49.7151.699.407
bernhard.rupp@ittcorp.com

Asia:
Henry Li
86.755.27267826
henry.li@ittcorp.com

Japan:
Takashi Goto
81.46.257.2012
takashi.goto@ittcorp.com