

MATERIAL NUMBER	# OF COLUMNS	# OF DIFF PAIR	DIM "A" MAX	DIM "B"	PTH ϕ
76150-**-10	10	60	26.60	17.10	0.46 ± 0.05
76150-**-14	14	84	34.20	24.70	
76150-**-16	16	96	38.00	28.50	
76150-**-20	10	60	26.60	17.10	0.39 ± 0.05
76150-**-24	14	84	34.20	24.70	
76150-**-26	16	96	38.00	28.50	

76150-****

5 = RIGHT GUIDED LEAD-FREE
POLARIZATION KEY ORIENTATION
0 = NO KEY
1 = A
2 = B
3 = C
4 = D
5 = E
6 = F
7 = G
8 = H
OF COLUMNS
10 = 10 COL 0.46 PTH
14 = 14 COL 0.46 PTH
16 = 16 COL 0.46 PTH
20 = 10 COL 0.39 PTH
24 = 14 COL 0.39 PTH
26 = 16 COL 0.39 PTH

SEE SHEET 1 EC NO: UCP2016-2564 DRWNG: VARVARA 2015/07/29 CHKD: APPR: TELO 2016/01/06	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE MM ONLY	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	$\nabla = 0$	4 PLACES \pm --- \pm ---	mm INCH	DRAWN BY JLAURX	DATE 2008/03/12	TITLE IMPACT 100 OHM DC 6 PAIR SIGNAL MODULE GUIDE RIGHT SALES DWG
	$\nabla = 0$	3 PLACES \pm --- \pm ---		CHECKED BY TELO	DATE 2008/03/12	
	$\nabla = 0$	2 PLACES ± 0.13 \pm ---	ANGULAR $\pm 1/2^\circ$	MATERIAL NO.	APPROVED BY JLAURX	DATE 2010/11/04
	1 PLACE ± 0.25 \pm ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SHEET NO. 2 OF 2