



Part Number: 9921

Hook- Up/ Lead Wire UL AWM Style 1007 & 1569, (1) 22 AWG (7x30) TC, PVC, 300V 80°C, 300V 105°C

[Request Sample](#)

Product Description

One 22 AWG stranded (7x30) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
22	7x30	TC - Tinned Copper	1

Conductor Count:	1
Conductor Size:	22 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.062 in	0.0165 in	0.015 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.062 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
15.25 Ohm/1000ft	6.2 Ohm/km

Shielding:	Unshielded
------------	------------

High Frequency (Nominal/Typical)

Nom. Insertion Loss
6.2 dB/100m
6.1 dB/100m

Unbalanced Crosstalk

Typical Unbalanced FEXT %
6.2 MHz

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient.	Single conductor in free air @ 30C ambient. 11 amps

Voltage

UL Voltage Rating
300 VRMS

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-20°C To +105°C

Mechanical Characteristics

Bulk Cable Weight:	3.5 lbs/1000ft
Min Bend Radius/Minor Axis:	6.25 in

Dimensions (WxHxD)

Length
6.25

Standards

UL Rating:	300V RMS, 80°C and 300V, 105°C
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 105°C
CSA Type:	TRSR-64
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
9921 010100	Black	
9921 0101000	Black	P
9921 0105000	Black	C
9921 013100	Blue, Dark	
9921 0131000	Blue, Dark	P
9921 0135000	Blue, Dark	C
9921 006100	Blue, Light	
9921 0061000	Blue, Light	P
9921 001100	Brown	
9921 0011000	Brown	P
9921 008100	Gray	
9921 0081000	Gray	P
9921 0085000	Gray	C P
9921 005100	Green, Dark	
9921 0051000	Green, Dark	P
9921 003100	Orange	
9921 0031000	Orange	P

9921 002100	Red	
9921 0021000	Red	P
9921 0025000	Red	C P
9921 007100	Violet	
9921 0071000	Violet	P
9921 009100	White	
9921 0091000	White	P
9921 004100	Yellow	
9921 0041000	Yellow	P
9921 0045000	Yellow	C

Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.
Footnote:	C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.