



NOTES:

1. TERMINAL MATERIAL: BRASS
2. TERMINAL FINISH: TIN PLATED
3. INSULATOR MATERIAL: POLYPROPYLENE, FLAMMABILITY UL94 V-2, UL RTI 105 °C, COLOR TRANSLUCENT
4. ASSEMBLY IS ROHS COMPLIANT.

| | | | | | | | | |
|--|--------------------------|--|---|------------------------------|---------------------|--------------|--|--|
| UPDATE TOLERANCES EC NO: WNA2011-0485 DRAWN: THRODAHL 2011/04/21 CHKD: JMACNEIL 2011/04/21 APPR: JMACNEIL 2011/04/21 | DESCRIPTION REV B1 | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | DIMENSION STYLE | SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION | |
| | | $\nabla=0$ $\nabla E=0$ | mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .005 2 PLACES ± 0.13 ± .01 1 PLACE ± 0.25 ± --- ANGULAR ± ---° | IN/MM | 2:1 | INCH | DRAWN BY DATE BRE 2001/06/06 CHECKED BY DATE HEB 2001/06/06 APPROVED BY DATE RWD 2001/06/06 | TITLE MALE, DOUBLE, QUICK DISCONNECT, INSULATED |
| | | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | MATERIAL NO. 191630178 | MOLEX INCORPORATED | SHEET NO. 1 OF 1 | | | |
| | | SIZE B | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | DOCUMENT NO. SD-19163-007 | MOLEX | | | |