

APPLICATOR PARTS LIST

TYPE LENGTHWISE SPLICE CONN. INSULATION PIERCING

AMP INCORPORATED HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER			42	GUARD- END		372886
2	INS. CRIMPER	1	1-570322-5	43	SPRING-SLIDE 3/4" O.D.	1	2-24017-7
3	ANVIL	1	1-471359-1	44	FEED PLATE RET.	1	372998
4	ANVIL SPACER			45			
5	SHEAR BLADE	1	455216-1	46			
6	FEED PLATE - FEED	1	471917-9	47			
7	SHEAR BLADE SPACER			48			
8	FRONT SHEAR PLATE			49	DEPRESSOR- TERMINAL		1-692142-1
9	REAR ANVIL SPACER PLT.			50			
10	FRONT ANVIL SPACER PLT.			51			
11	TOOL SPACER			52			
12	CRIMP SPACER			53			
13	FRONT STRIP GUIDE			54			
14	REAR STRIP GUIDE			55	SG. HD. SET SCR. (DEP.)	1	21077-8
				56	NUT, HEX.	1	22202-1
15	RAM	1	471057	57			
16	TOOL HOLDER			58			
17	ADJ. CRIMP MOUNT			59			
18	ADJ. BLOCK			60			
19	APPLICATOR MOUNT ASSY.	1	473933	61			
20	BASE PLATE			62			
21	BASE BLOCK			63			
22	STRIP GUIDE PLATE			64	MECH- FEED		1-692140-2
23	ANVIL HOLDER	1	374348-1	65	TENSION ADJ. PLATE	1	374999
24	AUX. ANVIL HOLDER				MISCELLANEOUS		
25	STRIPPER	1	376945	66			
26	STRIPPER MOUNT			67			
27	RETAINER PLATE			68			
28	STRIPPER MOUNT BRACKET			69			
29	STRIPPER BUSHING			70			
30	STOCK DRAG	1	372990	71			
31	STOCK DRAG WASHER NUT	1	21022-4	72			
32	STOCK DRAG- STUD	1	21015-8				
33	STOCK DRAG SPRING	1	23846-7				
34	STOCK DRAG ADJ. SCREW	2	372997				
35	FEED FINGER HOLDER						
36	FEED FINGER	1	811432-1				
37	FEED FINGER TIP						
38	FEED FINGER SPACER						
39	BASE CASTING	1	570238				
40	GUARD 460582-1	1	694395-1				
41	BRACKET- GUARD	1	376946				

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL SPEC 114-2088			485064
WIRE SIZE	CRIMP HEIGHT		
CRIMP	UNTIL TIGHT		
CRIMP	SIZE	TYPE	FEED
WIRE			
INSUL.	.080	0	.266
SLEEVED			
INSULATION RANGE	WIRE RANGE		
.050-.065	22		
EXPLODED VIEW			
A-6010-1 & -2			
REMARKS:			
THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.			
RECOMMENDED SPARE PARTS			
THIS APPLICATOR IS TO BE USED ON			
AMP-O-ELECTRIC 1-471273-3			
MECH. FEED			DIST.
			4
SERIAL NO.	DATE SHIPPED	DESIGNED	
		R. B. ... 3-26-71	
CUSTOMER NAME AND ADDRESS			CHK'D:
			6-26-71
			APP'D:
			6-26-71
APPLICATOR NUMBER	REV.	SHEET	
F1	566048-1	1 OF 1	

THIS IS A CONTROLLED DOCUMENT.

THIS DRAWING IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE. RELEASED FOR INSULATION. BY AMP INCORPORATED. ALL RIGHTS RESERVED. COPYRIGHT 2000