



SHELL	A±0.38	B±0.12	C±0.20	D±0.25	PART NUMBER	PART NUMBER
09	30.81	24.99	19.27	16.21	8657009S065TLF	8657L09S065TLF
15	39.14	33.32	27.50	24.54	8657015S065TLF	8657L15S065TLF
25	53.03	47.04	41.27	38.25	8657025S065TLF	8657L25S065TLF
37	69.32	63.50	57.70	54.71	8657037S065TLF	8657L37S065TLF

THREAD:UNC 4.40 THREAD:M3

NOTE:RoHS INFORMATIONS

- The "LF" product meets European union Directives and other country regulations as described in GS-22-008.
- The product is not intended to be exposed to a manufacturing solder process.
- Packaging spec: see GS-14-920.

MARKING

- Complete reference+FCI for shells 15-25-37
- Partial reference+FCI for shells 9: 865709S065LF with or without accessories

ELECTRICAL DATA

- Max current rating per contacts: 1.5A
- Contact resistance $\leq 10\text{m}\Omega$
- Insulation resistance >5000M Ω
- TEST VOLTAGE contact/contact >1000V
- Finish on contact area:gold over nickel
- Finish on terminalson end : bright tin over nickel

ENVIRONMENTAL DATA

- Climatic category -55° C/125° C/21j
- Corrosion salt spray:24h

rev	ecn no	dr	date
A	LS06-0022	MPE	2006/11/03
B	LS06-0101	MPE	2006/06/27
C	LS07-0041	MPE	2007/02/12
D	LS08-0159	MPE	2008/07/08
-	-	-	-
-	-	-	-
-	-	-	-

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection mm
TOLERANCES UNLESS OTHERWISE SPECIFIED				size A3
Dr	PESSON	2006/11/03	0.X	±0.1
Eng	PESSON	2006/11/03	0.XX	±0.1
Chr	LEGARE	2006/11/03	0.XXX	±0.1
Appr	LEGARE	2006/11/03	Product family D-SUB Spec ref -	
FCJ		SUB CONNECTOR IDC		Rev. D
title FOR FLAT CABLE		dwg no C01-8657-0612		Scale 2
catalog no		CUSTOMER		sheet 1 of 1