

## RJ45 connector - CUC-V14-C1ZNI-B/R4IE8 - 1408011

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 26 ... 24 AWG, for cable diameter of 5.5 mm ... 10 mm, cable outlet at the bottom

### Product Features

- Push-pull ADVANCE connector
- Locking system to prevent inadvertent removal
- Protected data transmission, thanks to 360° shielding concept
- High resistance to ESD and EMC for reliable transmission



### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	120.0 g
Custom tariff number	85367000
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Number of positions	8
Connection profile	RJ45
Locking type	Push Pull
Insertion/withdrawal cycles	≥ 750
Connection method	IDC fast connection
Connection cross section AWG	26 ... 24 (solid)
	26 ... 24 (stranded)
Max. cable diameter	5.5 mm ... 10 mm
External cable diameter	5.5 mm ... 10 mm

# RJ45 connector - CUC-V14-C1ZNI-B/R4IE8 - 1408011

## Technical data

### Mechanical characteristics

Cable exit	Bottom
------------	--------

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-10 °C ... 40 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Material data

Housing material	Zinc die-cast
Housing surface material	Nickel-plated

### Electrical characteristics

Number of positions	8
Rated current	1.75 A
Dielectric strength	800 V (In accordance with DIN/EN 60603-7)

### Standards and Regulations

Standards/regulations	IEC PAS 61076-3-117
-----------------------	---------------------

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27189239
eCl@ss 5.1	27189239
eCl@ss 6.0	27144001
eCl@ss 7.0	27144001
eCl@ss 8.0	27440101

### ETIM

ETIM 3.0	EC000007
ETIM 4.0	EC000489
ETIM 5.0	EC002636

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501

## RJ45 connector - CUC-V14-C1ZNI-B/R4IE8 - 1408011

### Classifications

#### UNSPSC

UNSPSC 13.2	31261501
-------------	----------