



LOW COST DATA ENTRY KEYBOARD

G83-6000



Available Part Numbers

G83-6101LADUS	101 Key, Beige, AT
G83-6101LPDUS	101 Key, Beige, PS/2
G83-6104LANUS	104 Key, Beige, AT
G83-6104LPNUS	104 Key, Beige, PS/2
G83-6104LANUS-0	104 Key, Light Grey, AT
G83-6104LPNUS-0	104 Key, Light Grey, PS/2
G83-6104LUNUS-0	104 Key, Light Grey, USB
G83-6104LRNUS-2	104 Key, Black, PS/2

Colors

Light Grey, Beige, Black

Dimensions

L x W x H = 18.03" x 6.69" x 1.37"

Keys

101 Key
104 Key Windows Compatible
Laser Printed

Keyswitch Technology

NTK; Rubber Sheet and Membrane

Interfaces

AT , PS/2, USB

Optional Features

Multiple Languages Available

Power Supply

+5V/DC \pm 5%, 35mA typical
USB Hubless max 100mA

Temperature

Storage Range: -4°F to +140°F
Operating Range: +32°F to +122°F

Reliability

MCBF: 1×10^9 operations
MTBF: > 80, hours; Operating Life of Individual
Keys: > 20 million actuations



FCC Part 15 Subpart
B Class B

CISPR 22 EN 550 22

Cherry Electrical Products

Phone: 800 510 1689
Web: www.cherrycorp.com