

Flat Cable EMI Suppression Cores (2643163951)



Part Number: 2643163951

43 SPLIT FLAT CABLE CORE

Explanation of Part Numbers:

- Digits 1 & 2 = Product Class
- Digits 3 & 4 = Material Grade

Flat cable suppression core can accommodate multi- conductors flat cables, in widths from 12.7 mm (0.500") up to 77 mm (3.0"). These flat cable cores are available in two ferrite material grades to reduce conducted EMI from 1 MHz to hundreds of MHz.

Clip Part Number: 0199001401 , 0199016551

Our Expanded Cable & Suppressor Kit (part number 0199000005) contains a selection of these flat cable cores and clips.

Flat Cable Cores are available in selected sizes in the Flex Circuit & Ribbon Cable Core Kit (part number 0199000038).

Assembly clips are available for most of the split flat cable cores. See section Flat Cable Cores Assembly clips.

Weight: 50 (g)

Dim	mm	mm tol	nominal inch	inch misc.	Cable Information			
A	63.5	±1.30	2.5	=	Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores
B	52.1	±1.10	2.05	=	0	51.00 x 1.30	-	-
C	28.6	±0.80	1.125	=				
D	6.35	±0.25	0.25	=				
E	0.85	±0.20	0.033	=				

Chart Legend
+ Test frequency

•For assembly clips see Flat Cable Cores Assembly Clips

Typical Impedance (Ω)	
10 MHz	56
25 MHz ⁺	100
100 MHz ⁺	290
250 MHz	400

Flat cable suppression cores, split or single cores, are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is typically the listed impedance less 20%.

Centered, single turn impedance tests for the 31 and 43 material parts are performed on the 4193A Vector Impedance Analyzer. All tests are made with the shortest practical wire length.

