



#### General ordering data

Order No.	8028300000
Part designation	DKO 35 24VDC 3KHZ E:U
Version	Optos, 5...48 V DC , 20 mA , Screw connection
EAN	4008190183158
Qty.	10 pc(s).

#### Dimensions

Clamping range, nom.	4 mm <sup>2</sup>
Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>

#### temperature

Ambient temperature (operational)	-25 °C...+40 °C
Storage temperature	-40 °C...+85 °C

#### Approvals

Approvals institutes	GOSTME25; CE
----------------------	--------------

#### Control side

Input frequency, max.	3 kHz
Power rating	Max. 360 mW
Rated auxiliary voltage	No
Rated control voltage	24 V DC ±10 %
making voltage	approx. 19 V / 7.5 mA

#### General data

Conductor cross-section, flexible, max.	4 mm <sup>2</sup>
Solid, max.	4 mm <sup>2</sup>
Standards	EN 50178
Humidity	40°C / 93% rel. humidity, no condensation
Conductor connection system	Screw connection
DIN Rail compatibility	TS 35

**Insulation coordination (EN 50 178)**Clearance and creepage distances for control/load  $\geq 4$  mm side

Overvoltage category	III
Pollution severity	2
Protective separation acc. to VDE 0106	No
Rated impulse withstand voltage	4 kV
Rated voltage	300 V

**Load side**

Protective circuit	Diode
Pulse duty factor (gen.)	1:2
Rated auxiliary voltage	No
Rated switching current	20 mA
Rated switching voltage	5...48 V DC
Short-circuit-proof	No
Status indicator load side	Green LED
Switch-off delay	Approx. 80 $\mu$ s
Switch-on delay	Approx. 50 $\mu$ s
Voltage drop at max. load	$\leq 900$ mV

**Classifications**

ETIM20	EC001504
ETIM30	EC001504
eClass 4.1	27-27-09-00
eClass 5.0	27-27-09-90
eClass 5.1	27-27-09-90
eClass 6.0	27-14-11-20

**Similar products**

Order No.	Part designation	Version
8018630000	DKO 35 5VDC	Optos, 5...48 V DC , 20 mA , Screw connection
8019590000	DKO 35 24VDC E:U	Optos, 5...48 V DC , 500 mA , Screw connection
8248790000	DKO 35 24VDC 3KHZ E:U	Optos, 5...48 V DC , 20 mA , Screw connection
8215630000	DKO 35 24VDC E:O	Optos, 5...48 V DC , 500 mA , Screw connection
8008150000	DKO 35 24VUC	Optos, 5...48 V DC , 20 mA , Screw connection
8215640000	DKO 35 24VDC 3KHZ E:O	Optos, 5...48 V DC , 20 mA , Screw connection
8025910000	DKO 35 48VUC	Optos, 5...48 V DC , 100 mA , Screw connection
8077860000	DKO 35 115VUC	Optos, 5...48 V DC , 50 mA , Screw connection
8008160000	DKO 35 230VUC	Optos, 5...48 V DC , 20 mA , Screw connection