



示意图 SCHEMATIC

安装孔 PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30_V 0.3_A
初期接触电阻 Initial Contact Resistance	30_mΩ Max.
绝缘电阻 Insulation Resistance	DC500_V 60_Sec. 100_MΩ Min.
抗电强度 Dielectric Voltage	AC 500_V (50~60HZ) 60_Sec.
操作力 Operating Force (gf)	A → B 250 ± 100 B → A 250 ± 100
负荷寿命 Operating Life With Load	10,000 Cycles

序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS
6	弹簧 SPRING	STEEL	1	NATURAL
5	端子 TERMINAL	C2680R	3	Ag PLATED
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW
3	接触片 CONTACT	COPPER WIRE	1	Ag PLATED
2	胶柄 KNOB	P B T	1	G 2 - 9
1	铁壳 FRAME	S P C C	1	Sn PLATED

标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
A02	接触阻抗更改为初期接触电阻 机械寿命更改为负荷寿命	刘红梅	06-07-07
A01	修改见 ①	张渠江	2005/4/29

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE		SIDE KNOB SLIDE SWITCH		ITEM NO		SK-12F17-G	
UNDER 1	± 0.10	DRAWN	刘红梅	06-07-07	VERSION	A02	PAGE	1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-07-07	SCALE		UNIT	mm	
OVER 10	± 0.50	APPROVED	林高全	06-07-10	PROJECTION				

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.