

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
FT	0	V2	REVISED PER ECO-11-004917	11MAR11	RK HMR

NOTES:

1 POLYOLEFIN, BLACK.  
 2 NYLON, BLACK.  
 3 NOMINAL WALL THICKNESS, EXPANDED.  
 4 LENGTH OF SEALANT.  
 5 EXPANDED INSIDE DIAMETER.  
 6 12.70[.500] MAXIMUM RECOVERED INSIDE DIAMETER.  
 7. ASSEMBLY WILL PASS 0.0703 KG PER SQ CENTIMETER [ONE POUND PER SQ IN.] WATER PRESSURE TEST.  
 8 121°C [250°F] SHRINK TEMPERATURE.  
 9. -55°C TO 110°C [-67°F TO 230°F] OPERATING TEMPERATURE.  
 10. THIS PART WILL ACCOMODATE  $\phi 13.97 - \phi 31.75$  [ $\phi .550 - \phi 1.250$ ] CABLE RANGE.  
 11 NO SEALANT APPLIED.  
 12 ACTUAL SHAPE MAY VARY DUE TO PROCESS VARIANCE.  
 13 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

13 OBSOLETE	1 7/16-18 UNEF-2B	54012-6
11	1 3/8-18 UNEF-2B	54012-5
11	1 7/16-18 UNEF-2B	54012-4
13 OBSOLETE	1 3/16-18 UNEF-2B	54012-3
	1 3/8-18 UNEF-2B	54012-1
THREAD "A"		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.REIFSNYDER 10 APR 96	TE Connectivity	
DIMENSIONS: INCHES		CHK R.STONE 15 APR 95	NAME STRN RELIEF ASSY, SHELL SIZE 23, CPC	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD T.A.WETZEL 03 MAY 96	SIZE A2	CAGE CODE 00779
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC -	DRAWING NO C=54012	RESTRICTED TO -
MATERIAL TUBING: 1 SLEEVE: 2		FINISH -	WEIGHT -	SCALE 2:1
CUSTOMER DRAWING			SHEET 1 of 1	REV V2

1471-9 (3/11)

54012

A