



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
010	RELEASED	3/22/95	M.A.

DESIGN CONTROL REQUIRED

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
COMPONENT	MATERIAL	FINISH

NOTES:

- DESIGNED FOR USE WITH .085 DIA SEMI-RIGID CABLE
- CAPTURED CENTER CONTACT

CABLE ENTRY DIAMETER MINIMUM	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ± .005 ± 1°	DRAWN BY <i>M.A.</i> DATE 3/22/95	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
HOUSING	.089	CHECKED BY	AMP TITLE OSM STRAIGHT CABLE JACK DIRECT SOLDER ATTACHMENT		
CONTACT	.021	APPD BY			
		USE ASS'Y PROCEDURE	NO. AP. 408-04833 (20-010)	SIZE B	CODE IDENT NO. 26805
				SCALE 5:1	1250-1989-00
					REV 010
					SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1046286-1
SHEET 1 OF 1 REV A