

Article Number: 557-00021

Spirit Self-Laminating Printer Label, 1.0" X .5" X 1.54", Vinyl, White, 250/RL



Download spec sheet

Base Data

Local Order Number TAGH22-100

Type TAGH22

Color White (WH)

Features and Benefits

- HellermannTyton 100 self-laminating vinyl utilizes an aggressive acrylic adhesive that allows the label to stay wrapped on wire gauges as small as .06" in diameter without starting to unwrap or flag.
- The label material is best printed with HellermannTyton HHHST series ribbons on the Spirit portable printing system for optimal print clarity.
- All Spirit self-laminating labels meet the requirements of UL-969 STANDARD FOR MARKING AND LABELING SYSTEMS edition - 4, under UL file number MH18396 to achieve long label life and print durability when used indoors or outdoors.

Color Marking Field White (WH)

Product Description The HellermannTyton Spirit printing system is easy to use and features a "What You See Is What You Get" (WYSIWYG) user interface that shows the outline of the label on the LCD screen for quick and easy editing and printing. The Spirit 2100 provides a fast, high quality, thermal transfer printing of labels that are designed to survive industrial environments. A wide variety of label materials, sizes and types are available to fit most applications.

Mounting method Identification ETIM Pasting / Stick

Short Description Spirit Self-Laminating Printer Label, 1.0" X .5" X 1.54", Vinyl, White, 250/RL

Product Dimensions

Length L (Imperial) 0.5 "

Length L (Metric) 12.7 mm

Variant Roller form

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Height H2 (Imperial) 1.435 "

Height H2 (Metric) 36.5 mm

Height of printable area (metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.13 "

Bundle Diameter Min. (Metric) 3.40 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.50 mm

Print Method Thermal Transfer

Width of Liner WL (imperial) 1.125 "

Width of Liner WL (metric) 28.57 mm

Logistics and Packaging

Quantity Per reel
Package Quantity 250
Package Quantity (Metric) 250
Carton Quantity 1
Weight (Metric) 0.3 kg

Material and Specifications

Material Type 100, Vinyl (PVC), white (WH), self laminating
Material Shortcut 100
Adhesive Acrylic
Adhesive Shortcut Acrylic
Adhesive Operating Temperature -40°F to +194°F (-40°C to +90°C)
Operating Temperature -40°F to +176°F (-40°C to +80°C)
ROHS Compliant Yes
Certification/Specification UL-Recognized