

Important notice

Dear Customer,

On 7 February 2017 the former NXP Standard Product business became a new company with the tradename **Nexperia**. Nexperia is an industry leading supplier of Discrete, Logic and PowerMOS semiconductors with its focus on the automotive, industrial, computing, consumer and wearable application markets

In data sheets and application notes which still contain NXP or Philips Semiconductors references, use the references to Nexperia, as shown below.

Instead of <http://www.nxp.com>, <http://www.philips.com/> or <http://www.semiconductors.philips.com/>, use <http://www.nexperia.com>

Instead of sales.addresses@www.nxp.com or sales.addresses@www.semiconductors.philips.com, use salesaddresses@nexperia.com (email)

Replace the copyright notice at the bottom of each page or elsewhere in the document, depending on the version, as shown below:

- © NXP N.V. (year). All rights reserved or © Koninklijke Philips Electronics N.V. (year). All rights reserved

Should be replaced with:

- © **Nexperia B.V. (year). All rights reserved.**

If you have any questions related to the data sheet, please contact our nearest sales office via e-mail or telephone (details via salesaddresses@nexperia.com). Thank you for your cooperation and understanding,

Kind regards,

Team Nexperia

74LVC273

Octal D-type flip-flop with reset; positive-edge trigger

Rev. 6 — 31 December 2012

Product data sheet

1. General description

The 74LVC273 has eight edge-triggered, D-type flip-flops with individual D_n inputs and Q_n outputs. The common clock (CP) and master reset ($\overline{\text{MR}}$) inputs load and reset (clear) all flip-flops simultaneously. The state of each D_n input, one set-up time before the LOW-to-HIGH clock transition, is transferred to the corresponding output (Q_n) of the flip-flop. All outputs will be forced LOW independently of clock or data inputs by a LOW voltage level on the $\overline{\text{MR}}$ input.

The device is useful for applications where the true output only is required and the clock and master reset are common to all storage elements.

2. Features and benefits

- Wide supply voltage range from 1.2 V to 3.6 V
- Inputs accept voltages up to 5.5 V
- CMOS low power consumption
- Direct interface with TTL levels
- Output drive capability 50 Ω transmission lines at +85 °C
- Complies with JEDEC standard:
 - ◆ JESD8-7A (1.65 V to 1.95 V)
 - ◆ JESD8-5A (2.3 V to 2.7 V)
 - ◆ JESD8-C/JESD36 (2.7 V to 3.6 V)
- ESD protection:
 - ◆ HBM JESD22-A114F exceeds 2000 V
 - ◆ MM JESD22-A115-B exceeds 200 V
 - ◆ CDM JESD22-C101E exceeds 1000 V
- Specified from -40 °C to +85 °C and -40 °C to +125 °C



3. Ordering information

Table 1. Ordering information

| Type number | Package | | | Version |
|-------------|-------------------|----------|---|----------|
| | Temperature range | Name | Description | |
| 74LVC273D | -40 °C to +125 °C | SO20 | plastic small outline package; 20 leads; body width 7.5 mm | SOT163-1 |
| 74LVC273DB | -40 °C to +125 °C | SSOP20 | plastic shrink small outline package; 20 leads; body width 5.3 mm | SOT339-1 |
| 74LVC273PW | -40 °C to +125 °C | TSSOP20 | plastic thin shrink small outline package; 20 leads; body width 4.4 mm | SOT360-1 |
| 74LVC273BQ | -40 °C to +125 °C | DHVQFN20 | plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 20 terminals; body 2.5 × 4.5 × 0.85 mm | SOT764-1 |

4. Functional diagram




Fig 1. Logic symbol





Fig 2. IEC logic symbol

5. Pinning information

5.1 Pinning



5.2 Pin description

Table 2. Pin description

| Symbol | Pin | Description |
|------------------------|----------------------------|---|
| $\overline{\text{MR}}$ | 1 | master reset input (active LOW) |
| CP | 11 | clock input (LOW-to-HIGH; edge-triggered) |
| D[0:7] | 3, 4, 7, 8, 13, 14, 17, 18 | data input |
| Q[0:7] | 2, 5, 6, 9, 12, 15, 16, 19 | flip-flop output |
| GND | 10 | ground (0 V) |
| V _{CC} | 20 | supply voltage |

6. Functional description

Table 3. Function table^[1]

| Operating mode | Input | | | Output |
|----------------|------------------------|----|----|--------|
| | $\overline{\text{MR}}$ | CP | Dn | Qn |
| Reset (clear) | L | X | X | L |
| Load '1' | H | ↑ | h | H |
| Load '0' | H | ↑ | l | L |

- [1] H = HIGH voltage level
 L = LOW voltage level
 X = don't care
 h = HIGH voltage level one set-up time prior to the LOW-to-HIGH CP transition
 l = LOW voltage level one set-up time prior to the LOW-to-HIGH CP transition
 ↑ = LOW-to-HIGH clock transition

7. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|-----------|-------------------------|-------------------------------|----------|----------------|------|
| V_{CC} | supply voltage | | -0.5 | +6.5 | V |
| I_{IK} | input clamping current | $V_I < 0$ V | -50 | - | mA |
| V_I | input voltage | | [1] -0.5 | +6.5 | V |
| I_{OK} | output clamping current | $V_O > V_{CC}$ or $V_O < 0$ V | - | 50 | mA |
| V_O | output voltage | | [2] -0.5 | $V_{CC} + 0.5$ | V |
| I_O | output current | $V_O = 0$ V to V_{CC} | - | ±50 | mA |
| I_{CC} | supply current | | - | 100 | mA |
| I_{GND} | ground current | | -100 | - | mA |
| T_{stg} | storage temperature | | -65 | +150 | °C |
| P_{tot} | total power dissipation | $T_{amb} = -40$ °C to +125 °C | [3] - | 500 | mW |

- [1] The minimum input voltage ratings may be exceeded if the input current ratings are observed.
 [2] The output voltage ratings may be exceeded if the output current ratings are observed.
 [3] For SO20 packages: above 70 °C the value of P_{tot} derates linearly with 8 mW/K.
 For (T)SSOP20 packages: above 60 °C the value of P_{tot} derates linearly with 5.5 mW/K.
 For DHVQFN20 packages: above 60 °C the value of P_{tot} derates linearly with 4.5 mW/K.

8. Recommended operating conditions

Table 5. Recommended operating conditions

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|----------|----------------|------------|------|-----|----------|------|
| V_{CC} | supply voltage | | 1.65 | - | 3.6 | V |
| | | functional | 1.2 | - | - | V |
| V_I | input voltage | | 0 | - | 5.5 | V |
| V_O | output voltage | | 0 | - | V_{CC} | V |

Table 5. Recommended operating conditions ...continued

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---------------------|-------------------------------------|--|-----|-----|------|------|
| T_{amb} | ambient temperature | in free air | -40 | - | +125 | °C |
| $\Delta t/\Delta V$ | input transition rise and fall rate | $V_{CC} = 1.65\text{ V to }2.7\text{ V}$ | 0 | - | 20 | ns/V |
| | | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ | 0 | - | 10 | ns/V |

9. Static characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|-----------------|---|--|----------------------|--------------------|----------------------|----------------------|----------------------|---------------|
| | | | Min | Typ ^[1] | Max | Min | Max | |
| V_{IH} | HIGH-level input voltage | $V_{CC} = 1.2\text{ V}$ | 1.08 | - | - | 1.08 | - | V |
| | | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | $0.65 \times V_{CC}$ | - | - | $0.65 \times V_{CC}$ | - | V |
| | | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$ | 1.7 | - | - | 1.7 | - | V |
| | | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ | 2.0 | - | - | 2.0 | - | V |
| V_{IL} | LOW-level input voltage | $V_{CC} = 1.2\text{ V}$ | - | - | 0.12 | - | 0.12 | V |
| | | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | - | - | $0.35 \times V_{CC}$ | - | $0.35 \times V_{CC}$ | V |
| | | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$ | - | - | 0.7 | - | 0.7 | V |
| | | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ | - | - | 0.8 | - | 0.8 | V |
| V_{OH} | HIGH-level output voltage | $V_I = V_{IH}$ or V_{IL} | | | | | | |
| | | $I_O = -100\ \mu\text{A}; V_{CC} = 1.65\text{ V to }3.6\text{ V}$ | $V_{CC} - 0.2$ | - | - | $V_{CC} - 0.3$ | - | V |
| | | $I_O = -4\text{ mA}; V_{CC} = 1.65\text{ V}$ | 1.2 | - | - | 1.05 | - | V |
| | | $I_O = -8\text{ mA}; V_{CC} = 2.3\text{ V}$ | 1.8 | - | - | 1.65 | - | V |
| | | $I_O = -12\text{ mA}; V_{CC} = 2.7\text{ V}$ | 2.2 | - | - | 2.05 | - | V |
| | | $I_O = -18\text{ mA}; V_{CC} = 3.0\text{ V}$ | 2.4 | - | - | 2.25 | - | V |
| V_{OL} | LOW-level output voltage | $V_I = V_{IH}$ or V_{IL} | | | | | | |
| | | $I_O = 100\ \mu\text{A}; V_{CC} = 1.65\text{ V to }3.6\text{ V}$ | - | - | 0.2 | - | 0.3 | V |
| | | $I_O = 4\text{ mA}; V_{CC} = 1.65\text{ V}$ | - | - | 0.45 | - | 0.65 | V |
| | | $I_O = 8\text{ mA}; V_{CC} = 2.3\text{ V}$ | - | - | 0.6 | - | 0.8 | V |
| | | $I_O = 12\text{ mA}; V_{CC} = 2.7\text{ V}$ | - | - | 0.4 | - | 0.6 | V |
| | $I_O = 24\text{ mA}; V_{CC} = 3.0\text{ V}$ | - | - | 0.55 | - | 0.8 | V | |
| I_I | input leakage current | $V_{CC} = 3.6\text{ V}; V_I = 5.5\text{ V or GND}$ | - | ± 0.1 | ± 5 | - | ± 20 | μA |
| I_{CC} | supply current | $V_{CC} = 3.6\text{ V}; V_I = V_{CC}$ or $\text{GND}; I_O = 0\text{ A}$ | - | 0.1 | 10 | - | 40 | μA |
| ΔI_{CC} | additional supply current | per input pin; $V_{CC} = 2.7\text{ V to }3.6\text{ V}; V_I = V_{CC} - 0.6\text{ V}; I_O = 0\text{ A}$ | - | 5 | 500 | - | 5000 | μA |
| C_I | input capacitance | $V_{CC} = 0\text{ V to }3.6\text{ V}; V_I = \text{GND to }V_{CC}$ | - | 5.0 | - | - | - | pF |

[1] All typical values are measured at $V_{CC} = 3.3\text{ V}$ (unless stated otherwise) and $T_{amb} = 25\text{ °C}$.

10. Dynamic characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V). For test circuit see [Figure 8](#).

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|------------------|-------------------------------|---|------------------|--------------------|------|-------------------|------|------|
| | | | Min | Typ ^[1] | Max | Min | Max | |
| t _{pd} | propagation delay | CP to Qn; see Figure 5 ^[2] | | | | | | |
| | | V _{CC} = 1.2 V | - | 18 | - | - | - | ns |
| | | V _{CC} = 1.65 V to 1.95 V | 2.5 | 9.7 | 19.2 | 2.5 | 22.2 | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 1.8 | 4.9 | 9.9 | 1.8 | 11.4 | ns |
| | | V _{CC} = 2.7 V | 1.5 | 4.5 | 8.4 | 1.5 | 10.5 | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.5 | 4.1 | 8.2 | 1.5 | 10.5 | ns |
| t _{PHL} | HIGH to LOW propagation delay | MR to Qn; see Figure 6 | | | | | | |
| | | V _{CC} = 1.2 V | - | 18 | - | - | - | ns |
| | | V _{CC} = 1.65 V to 1.95 V | 2.4 | 10.2 | 20.4 | 2.4 | 23.5 | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 1.7 | 5.2 | 10.5 | 1.7 | 12.1 | ns |
| | | V _{CC} = 2.7 V | 1.5 | 4.7 | 8.9 | 1.5 | 11.5 | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.5 | 4.3 | 8.7 | 1.5 | 11.0 | ns |
| t _w | pulse width | clock HIGH or LOW; see Figure 5 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 6.0 | - | - | 6.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 5.0 | - | - | 5.0 | - | ns |
| | | V _{CC} = 2.7 V | 5.0 | 1.8 | - | 5.0 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 4.0 | 1.2 | - | 4.0 | - | ns |
| | | master reset LOW; see Figure 6 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 6.0 | - | - | 6.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 5.0 | - | - | 5.0 | - | ns |
| | | V _{CC} = 2.7 V | 5.0 | 1.7 | - | 5.0 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 4.0 | 1.2 | - | 4.0 | - | ns |
| t _{rec} | recovery time | MR to CP; see Figure 6 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 2.0 | - | - | 2.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 2.0 | - | - | 2.0 | - | ns |
| | | V _{CC} = 2.7 V | 2.0 | -1.0 | - | 2.0 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 2.0 | -1.0 | - | 2.0 | - | ns |
| t _{su} | set-up time | Dn to CP; see Figure 7 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 5.0 | - | - | 5.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 3.5 | - | - | 3.5 | - | ns |
| | | V _{CC} = 2.7 V | 3.0 | 1.0 | - | 3.0 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.0 | 0.0 | - | 1.0 | - | ns |
| t _h | hold time | Dn to CP; see Figure 7 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 3.0 | - | - | 3.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 2.5 | - | - | 2.5 | - | ns |
| | | V _{CC} = 2.7 V | 2.0 | -0.2 | - | 2.0 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.0 | 0.0 | - | 1.0 | - | ns |


Table 7. Dynamic characteristics ...continued


Voltages are referenced to GND (ground = 0 V). For test circuit see [Figure 8](#).

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit | |
|--------------------|-------------------------------|--|------------------|--------------------|-----|-------------------|-----|------|----|
| | | | Min | Typ ^[1] | Max | Min | Max | | |
| f _{max} | maximum frequency | see Figure 5 | | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 80 | - | - | 64 | - | MHz | |
| | | V _{CC} = 2.3 V to 2.7 V | 100 | - | - | 80 | - | MHz | |
| | | V _{CC} = 2.7 V | 150 | - | - | 150 | - | MHz | |
| | | V _{CC} = 3.0 V to 3.6 V | 150 | 230 | - | 150 | - | MHz | |
| t _{sk(o)} | output skew time | V _{CC} = 3.0 V to 3.6 V | [3] | - | - | 1.0 | - | 1.5 | ns |
| C _{PD} | power dissipation capacitance | per flip-flop; V _I = GND to V _{CC} | [4] | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | - | 14.0 | - | - | - | pF | |
| | | V _{CC} = 2.3 V to 2.7 V | - | 17.7 | - | - | - | pF | |
| | | V _{CC} = 3.0 V to 3.6 V | - | 21.0 | - | - | - | pF | |

- [1] Typical values are measured at T_{amb} = 25 °C and V_{CC} = 1.2 V, 1.8 V, 2.5 V, 2.7 V and 3.3 V respectively.
- [2] t_{pd} is the same as t_{PLH} and t_{PHL}.
- [3] Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.
- [4] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).
 $P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:
 f_i = input frequency in MHz; f_o = output frequency in MHz
 C_L = output load capacitance in pF
 V_{CC} = supply voltage in Volt
 N = number of inputs switching
 Σ(C_L × V_{CC}² × f_o) = sum of the outputs


11. Waveforms





Measurement points are given in [Table 8](#).
 V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig 6. Master reset (\overline{MR}) pulse width, the master reset to output (Q_n) propagation delays, and the master reset to clock (CP) recovery time





Measurement points are given in [Table 8](#).
 V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.
 The shaded areas indicate when the input is permitted to change for predictable output performance.

Fig 7. Data set-up and hold times for the data input (D_n)

Table 8. Measurement points

| Supply voltage | Input | | Output | | |
|------------------|-----------------|-----------------------|-----------------------|--------------------------|--------------------------|
| V _{CC} | V _I | V _M | V _M | V _X | V _Y |
| 1.2 V | V _{CC} | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} + 0.15 V | V _{OH} - 0.15 V |
| 1.65 V to 1.95 V | V _{CC} | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} + 0.15 V | V _{OH} - 0.15 V |
| 2.3 V to 2.7 V | V _{CC} | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} + 0.15 V | V _{OH} - 0.15 V |
| 2.7 V | 2.7 V | 1.5 V | 1.5 V | V _{OL} + 0.3 V | V _{OH} - 0.3 V |
| 3.0 V to 3.6 V | 2.7 V | 1.5 V | 1.5 V | V _{OL} + 0.3 V | V _{OH} - 0.3 V |



Test data is given in [Table 9](#).

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to output impedance Z_o of the pulse generator.

Fig 8. Load circuitry for switching times

Table 9. Test data

| Supply voltage | Input | | Load | | V _{EXT} | | |
|------------------|-----------------|---------------------------------|----------------|----------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | V _I | t _r , t _f | C _L | R _L | t _{PLH} , t _{PHL} | t _{PZL} , t _{PZL} | t _{PHZ} , t _{PZH} |
| 1.2 V | V _{CC} | ≤ 2 ns | 30 pF | 1 kΩ | open | 2 × V _{CC} | GND |
| 1.65 V to 1.95 V | V _{CC} | ≤ 2 ns | 30 pF | 1 kΩ | open | 2 × V _{CC} | GND |
| 2.3 V to 2.7 V | V _{CC} | ≤ 2 ns | 30 pF | 500 Ω | open | 2 × V _{CC} | GND |
| 2.7 V | 2.7 V | ≤ 2.5 ns | 50 pF | 500 Ω | open | 2 × V _{CC} | GND |
| 3.0 V to 3.6 V | 2.7 V | ≤ 2.5 ns | 50 pF | 500 Ω | open | 2 × V _{CC} | GND |

12. Package outline

SO20: plastic small outline package; 20 leads; body width 7.5 mm

SOT163-1




Fig 9. Package outline SOT163-1 (SO20)

SSOP20: plastic shrink small outline package; 20 leads; body width 5.3 mm

SOT339-1




Fig 10. Package outline SOT339-1 (SSOP20)

TSSOP20: plastic thin shrink small outline package; 20 leads; body width 4.4 mm

SOT360-1




Fig 11. Package outline SOT360-1 (TSSOP20)

DHVQFN20: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 20 terminals; body 2.5 x 4.5 x 0.85 mm

SOT764-1




Fig 12. Package outline SOT764-1 (DHVQFN20)

13. Abbreviations

Table 10. Abbreviations

| Acronym | Description |
|---------|-----------------------------|
| CDM | Charged Device Model |
| DUT | Device Under Test |
| ESD | ElectroStatic Discharge |
| HBM | Human Body Model |
| MM | Machine Model |
| TTL | Transistor-Transistor Logic |

14. Revision history

Table 11. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|----------------|--|-----------------------|---------------|--------------|
| 74LVC273 v.6 | 20121231 | Product data sheet | - | 74LVC273 v.5 |
| Modifications: | <ul style="list-style-type: none"> General description changed (errata). | | | |
| 74LVC273 v.5 | 20121206 | Product data sheet | - | 74LVC273 v.4 |
| Modifications: | <ul style="list-style-type: none"> The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. Legal texts have been adapted to the new company name where appropriate. Table 4, Table 5, Table 6, Table 7, Table 8 and Table 9: values added for lower voltage ranges. | | | |
| 74LVC273 v.4 | 20040312 | Product specification | - | 74LVC273 v.3 |
| 74LVC273 v.3 | 20031030 | Product specification | - | 74LVC273 v.2 |
| 74LVC273 v.2 | 19980520 | Product specification | - | 74LVC273 v.1 |
| 74LVC273 v.1 | 19960606 | Product specification | - | - |

15. Legal information

15.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

15.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

15.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond

NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

16. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

17. Contents

| | | |
|-----------|---|-----------|
| 1 | General description | 1 |
| 2 | Features and benefits | 1 |
| 3 | Ordering information | 2 |
| 4 | Functional diagram | 2 |
| 5 | Pinning information | 3 |
| 5.1 | Pinning | 3 |
| 5.2 | Pin description | 3 |
| 6 | Functional description | 4 |
| 7 | Limiting values | 4 |
| 8 | Recommended operating conditions | 4 |
| 9 | Static characteristics | 5 |
| 10 | Dynamic characteristics | 6 |
| 11 | Waveforms | 7 |
| 12 | Package outline | 10 |
| 13 | Abbreviations | 14 |
| 14 | Revision history | 14 |
| 15 | Legal information | 15 |
| 15.1 | Data sheet status | 15 |
| 15.2 | Definitions | 15 |
| 15.3 | Disclaimers | 15 |
| 15.4 | Trademarks | 16 |
| 16 | Contact information | 16 |
| 17 | Contents | 17 |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2012.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 31 December 2012

Document identifier: 74LVC273