

INTERCONNECTS

SERIES 832 & 833 • 2mm GRID (.020" DIA. PINS), SHROUDED STRAIGHT, SURFACE MOUNT & RIGHT ANGLE • DOUBLE ROW STRIPS




FIG. 1




FIG. 2




FIG. 3





FIG. 4

- Shrouded pin interconnects available with straight Series 832...10-052 or surface mount 832...30-052 and use MM #3143 pins. Series 832...20-052 right angle interconnects use MM #3160 and #3161 pins. See page 214 for details
- Series 833...10-002 with keying features use MM #1802 and accept pin diameters from .015"-.025". See page 169 for details
- Receptacles use Hi-Rel, Low force, 4-finger BeCu #30 contact rated at 3 amps. See page 253 for details
- Insulators are high temperature thermoplastic, suitable for all soldering operations



ORDERING INFORMATION













FIG. 1	Series 832...10-052	Straight Pin Header
	832-10- <u> </u> -10-052000	
	Specify number of pins	004-100
FIG. 2	Series 832...20-052	Right Angle Pin Header
	832-10- <u> </u> -20-052000	
	Specify number of pins	004-100
FIG. 3	Series 832...30-052	Surface Mount Pin Header
	832-10- <u> </u> -30-052000	
	Specify number of pins	004-100
  		
SPECIFY PLATING CODE XX=		
Pin Plating	 10  10 μ" Au	

FIG. 4	Series 833...10-002	Double Row Keying Socket
	833-13- <u> </u> -10-002000	
	Specify number of pins	004-100
  		
SPECIFY PLATING CODE XX=		
Sleeve (Pin)	 10  10 μ" Au	
Contact (Clip)	 30  30 μ" Au	

