


## 4.7" Round LED Light Engine 60 Nichia LEDs Constant-Current DC Array

Intelligent Device  
**ECOSYSTEM**  
Classic

### Electrical Specifications


Driver Type:	Constant-Current
Drive Current:	450mA Nominal
Nom. Forward Voltage:	35.9V
Total Board Power:	16.2W Nominal
Life:	50,000 Hrs, 70% lumen maint. @ Ta max 40°C, used as specified
Max Junction Temp:	90°C
Max Test Point Temp:	80°C
Operating Temp:	-40°C to +60°C Ambient
Storage Temp:	-40°C to +80°C
Viewing Angle (FWHM):	120° Lambertian distribution
CRI:	83 typical



### 4.7 Inch Round DC LED Module @ 450mA

Model	Total Board Power (W)	Total Current (mA)	Color Temp (K)	Lumens (± 15%)	Board LPW
98021	16.2	450	2700	1,970	122
98022	16.2	450	3000	2,100	130
98023	16.2	450	3500	2,200	136
98024	16.2	450	4000	2,265	140
98027	16.2	450	5000	2,335	144

### Dimensions:



- Constant-Current DC Array, 12 LED Series x 5 Parallel Strings
- Designed for easy use in standard luminaires
- Tight LED pitch eliminates pixelization, no complex lens or optics required
- Color: ¼ ANSI Binning, 3 Step MacAdam Ellipse
- Suggested Applications: Commercial or Residential Downlights
- Customizable: Engines can be modified to your application. Contact us.
- Engineered by Norlux
- 5 yr. Warranty

### Connectivity Options

Suffix	Connection
(blank)	12 IN, #22 AWG Stranded Leads
-01	No Leads
-02	Push-in Connectors

For Poke-In Connectors, use #24-18 AWG stranded or solid wire

### CIE Chromaticity Coordinates:

#### 2700K

3 Step Macadams Ellipse

X	Y
0.4576	0.4183
0.4698	0.4212
0.4478	0.3999
0.4591	0.4025

#### 3000K

3 Step Macadams Ellipse

X	Y
0.4325	0.4101
0.4452	0.4146
0.4244	0.3923
0.4362	0.3965

#### 3500K

3 Step Macadams Ellipse

X	Y
0.4045	0.3975
0.4189	0.4044
0.3989	0.3819
0.412	0.3875

#### 4000K


3 Step Macadams Ellipse

X	Y
0.3783	0.3836
0.3909	0.3906
0.3746	0.3687
0.3864	0.3757

#### 5000K

3 Step Macadams Ellipse

X	Y
0.3408	0.3461
0.3485	0.3520
0.3416	0.3585
0.3499	0.3644



### Compatible TRP Drivers:

The drivers listed here are all compatible with this module. Choose the best driver for your application.

- LED12W-48-C0250
- LED20W-40-C0350-LE
- LED20W-40-C0350-TE
- LED20W-57-C0350
- LED20W-57-C0350-D
- LDC25W-048-C0450
- LED25W-56-C0450
- LED25W-56-C0450-D
- LED25W-56-C0450-HL-B
- LED25W-56-C0450-HL-S
- LED25W-56-C0450-HL-BD
- LED25W-56-C0450-HL-SD
- LED25W-072-C0350
- LED25W-072-C0350-D
- LED25W-062-C0400
- LED25W-062-C0400-D
- LED25W-072-C0350-LE
- LED25W-072-C0350-TE
- LEDDC25W-072-C0350
- LEDDC25W-072-C0350-D
- LED30W-085-C0350
- LED30W-085-C0350-D
- LED30W-075-C0400
- LED30W-075-C0400-D
- LED30W-066-C0450
- LED30W-066-C0450-D

### Step Dimming:


This Light Engine can be step-dimmed, with a recommended TRP dimmable driver and SD series step-dimming module. See the SD2 or SD3 data sheet for wiring information.

### Series/Parallel Configurations


**Parallel:** The positive and negative of one board is connected to the respective positive and negative of the next. Current adds, so the supply must be 2x the current for 2 boards.

**Series:** The negative of one board is connected to the positive of the next. Voltage adds, so the supply must be 2x the voltage for 2 boards.

#### Parallel



#### Series



### Maximum Run Lengths

The max number of boards wired in a chain (**series**) is limited by the max current rating of the first board wired to the driver. The sum of the board currents, in the chain, funnels through the first board. Multiple chains can connect directly to the power supply in parallel. See table for max chain length.

Product	Series/Parallel	Max Allowable Boards	
		High Current (Nom)	Low Current
4.7" Round	Series	7	N/A

### Mounting Notes

The LED assembly is supplied with mounting holes, per the dimensional drawing. It is important to mount the board in such a way as to maintain the Tc point below the max. The steady state thermals in application will dictate if the board needs to be mounted directly to metallic housing and/or include a thermal pad. For example fully enclosed recessed fixture will require better thermal mounting than an open air pendant.

### Thermal Application Notes

**This board requires additional heat sinking to run above 45°C ambient** at nominal specifications. Heat sink is also required when operated above specified drive currents.

### Maximum Current

**Max Current: 900mA**

**Voltage at max current: 40V, Power at max current: 36W**

The total maximum current reflects the LED maximum forward current only, without considering thermal needs. Driving the LEDs this hard will likely violate their thermal limits, depending on the application. **Tc point must remain at or below the max temperature, or the warranty will be voided.** Temperature is directly correlated to LED current.

### Static Sensitive Device

Handle only at static-safe work stations.

### Packaging

50 per box standard.