


RECOMMENDED PCB LAYOUT



CIRCUIT: SPST
CONTACT CONFIGURATION

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 50mA, @12V DC
5. CONTACT MATERIAL: GOLD
6. TRAVEL: 0.25±0.1mm
7. OPERATING FORCE: 160±50gf
8. CONTACT RESISTANCE: 100 milli-Ohms Max.
9. ELECTRICAL LIFE: 100,000 CYCLES MIN.
10. DESIGNATE MAJOR: ▲
11. ACTUATOR COLOR: (STD) BLACK

E-SWITCH®

TL 1105 D F160 R

REV.	ECN NO.	DESCRIPTION	DATE	CHKD
B	11541	REVISED AND REDRAWN	6/14/01	CJB
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED				

TITLE	SCALE	DATE	DR	DWG	REV
TL 1105 D F160 R	4:1	6/14/01	CJB	P060005	B