Noritake itron

CU209-TW200A

SIMPLIFIED DATASHEET

■ Features

20 character x 1 line display character module. Wide illuminating surface for enhanced visibility.

■ Outer dimension



Get full specification

Click here to go to request form.

Specifications

■ Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Power supply voltage	VCC	4.75	5.00	5.25	VDC	-

■ Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Input Voltage						
H	VIH	0.8VCC	-	VCC	VDC	Vcc=5.0V
L	VIL	0	-	0.3VCC		TA=25℃
Output Voltage						
H	VOH	VCC-1.5	-	-		IOH=-5mA
L	VOL	-	-	1.5		IOL=5mA
Power Supply Current	Icc	-	360	470	mADC	All dots ON

■ Optical Characteristics

Parameter	
Luminance	685 cd/m^2 Min.
Color of illumination	Green (Blue-Green)

■ Environmental Conditions

Parameter	
Operating Temperature	-40 ~ +85 degrees celsius
Storage Temperature	-40 ~ +85 degrees celsius
Operating Humidity	20 ~ 80% R.H. (non-condensing)
Vibration (Non operation)	10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z
Shock (non-operating)	980m/s^2 (100G) 9ms X-Y-Z, 3 times each direction

■ Physical Specifications

Parameter	
Number of Char.	20 (20 characters x 1 line)
Built-in Fonts	ANK, International Font
Character Format	5 x 7 dot matrix & Under line
Display Area	164.0 x 11.2 mm (X x Y)
Character Size	6.3 x 11.2 mm (X x Y)
Character Pitch	8.3 mm

■ Interface

Parallel, Asynchronous Serial (CMOS)

■ Pin Assignment (Parallel / Serial)

Pin No	Signal	Pin No	Signal
1	D7	2	D6
3	D5	4	D4
5	D3	6	D2
7	D1	8	D0
9	WR	10	CS
11	SIN/TO	12	BUSY
13	GND	14	GND
15	VCC	16	VCC

(Serial)

Pin No	Signal
1	VCC
2	SIN/T0
3	GND

Baud Rate Setting
19200bps*
9600bps
4800bps
2400bps
1200bps
600bps
(*:factory default)

■ Functions

Parameter
Auto initialized
Command Control
Blink speed control
Flicker less Mode / Quick Write Mode
etc.

RoHS COMPLIANT

Leaflet contents, and specifitaions and external appearance of products, may change without notice.
Please confirm product details in the specification.
(C)Copyright NORITAKE ITRON CORP.