



| | | | |
|------|------|------------|----|
| 21.6 | 17.2 | 52089-1619 | 16 |
| 20.6 | 16.2 | 52089-1519 | 15 |
| 15.6 | 11.2 | 52089-1019 | 10 |
| 13.6 | 9.2 | 52089-0819 | 8 |
| 12.6 | 8.2 | 52089-0719 | 7 |
| 10.6 | 6.2 | 52089-0519 | 5 |

- 注記 NOTES**
- △ CKT. NO. 1を基準に偶数番目のソルダーテール。
EVEN NUMBER SOLDER TAIL
 - △ CKT. NO. 1を基準に奇数番目のソルダーテール。
ODD NUMBER SOLDER TAIL
 - △ 接点部までの嵌合長さ。
LENGTH TO CONTACT POINT.
 - 4. 使用材料 MATERIAL
ハウジング : 66ナイロン, UL94V-0
HOUSING : 66NYLON, UL94V-0
アクチュエータ : ポリエステル, UL94V-0
ACTUATOR : POLYESTER, UL94V-0
ターミナル : リン青銅, ニッケル下地 錫・ピスマスメッキ
TERMINAL : PHOS-BRO. TIN-BISMUTM OVER NICKEL-PLATED
 - △ キングはソルダーテール△の両端のみに適用。
KINK APPLIES BOTH SIDE △ TERMINALS ONLY
 - 6. 本製品は 52089-** * 1.0 の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 52089-** * 1.0.

| | | | | | | | | | | | | | | | | | | |
|---|---|----------------------------|---|------------------------|------------------------|----------|---|----------|------|----------|-------|---------|------|---------|------|--|-------------------------------|--|
| REVISED EC NO: J2017-0269 IDRMNIGES 2016/11/17 CHKD: MSASAO APPR: MSASAO 2016/12/26 | GENERAL TOLERANCES (UNLESS SPECIFIED) | DIMENSION STYLE MM ONLY | SCALE 10:1 | DESIGN UNITS METRIC | THIRD ANGLE PROJECTION | | | | | | | | | | | | | |
| | <table border="1"> <tr> <td>0.25 UNDER</td> <td>±</td> </tr> <tr> <td>0.25 OVER</td> <td>±</td> </tr> <tr> <td>0.5 OVER</td> <td>±</td> </tr> <tr> <td>1.0 OVER</td> <td>±0.2</td> </tr> <tr> <td>3.0 OVER</td> <td>±0.25</td> </tr> <tr> <td>30 OVER</td> <td>±0.3</td> </tr> <tr> <td>ANGULAR</td> <td>±3 °</td> </tr> </table> | 0.25 UNDER | ± | 0.25 OVER | ± | 0.5 OVER | ± | 1.0 OVER | ±0.2 | 3.0 OVER | ±0.25 | 30 OVER | ±0.3 | ANGULAR | ±3 ° | DRAWN BY: J. SASAMO DATE: 2004/7/22 CHECKED BY: K. TOJO DATE: 2004/7/22 APPROVED BY: N. UKITA DATE: 2004/7/22 MATERIAL NO. | TITLE 1.0 FPC CONN ZIF R/A | -LEAD FREE- molex DOCUMENT NO. SD-52089-001 SHEET NO. 1 OF 1 |
| 0.25 UNDER | ± | | | | | | | | | | | | | | | | | |
| 0.25 OVER | ± | | | | | | | | | | | | | | | | | |
| 0.5 OVER | ± | | | | | | | | | | | | | | | | | |
| 1.0 OVER | ±0.2 | | | | | | | | | | | | | | | | | |
| 3.0 OVER | ±0.25 | | | | | | | | | | | | | | | | | |
| 30 OVER | ±0.3 | | | | | | | | | | | | | | | | | |
| ANGULAR | ±3 ° | | | | | | | | | | | | | | | | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | SIZE A3 | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | | | | | | | | | | | |