



- KEYS INSTALLED IN POSITIONS AS SHOWN IN TABLE.
  - CONTACTS ARE INCLUDED IN A CONTAINER WITHIN THE CONNECTOR PACKAGE FOR SHIPMENT.
  - ALL DIMENSIONS CONFORM TO MIL-C-81659 WITH EXCEPTION TO EMI SPRING FINGERS.
  - COAX/TRIAX CONTACTS TO BE PURCHASED SEPARATELY.
  - CONFORMS TO REQUIREMENTS OF MCDONNELL DOUGLAS 5M1972.
- △ CONNECTOR VIEW AND INSERT LAYOUT IS SHOWN FOR 449583-1.  
 △ MATING FACE SHOWN FOR REFERENCE ONLY.

PART NUMBER	CUSTOMER PART NUMBER	POLARIZING POSITION	MOD A	MOD B
449583-1	5M1972-01P02P	04	106P	36C7P
449583-2	5M1972-01P01P	04	106P	106P
449583-3	5M1972-01P03S	02	106P	32C2
449583-4	5M1972-04P01P	45	25C15	106P
449583-5	5M1972-02P01P	01	36C7P	106P
449583-6	5M1972-02P01PA	01	36C7P	106P

**OBSELETE**

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. ALEXANDER 4-17-96	<b>STE</b> TE Connectivity
DIMENSIONS: INCHES		CHK K. GUARAGNO 4-22-96	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K. GUARAGNO 4-22-96	NAME
0 PLC ± -		PRODUCT SPEC	ARINC 404 KIT, MME2P106P36C7P-0004 (204) WITH EMI FINGERS
1 PLC ± -		APPLICATION SPEC	SIZE
2 PLC ± -		WEIGHT	CAGE CODE
3 PLC ± .010 [0.25]		CUSTOMER DRAWING	DRAWING NO
4 PLC ± .0050		SCALE 2:1	RESTRICTED TO
ANGLES ± -		SHEET 1 OF 1	REV E