



WIRE BUNDLE DIA.  
.135 TO .475  
(3.5 TO 12.0)

.327 ±.002  
(8.3 ±.05)  
2X

Ø.187 ±.002  
(Ø4.8 ±.05)

Ø.078 ±.002  
(Ø2.0 ±.05)  
ANTI-ROTATION  
HOLES

.078  
(2.0)

RECOMMENDED  
MOUNTING PATTERN

NOTES:

1. MATERIAL: NYLON 66 (RMS-01).  
FLAME RETARDANT, NYLON (RMS-19).  
BY SPECIAL ORDER.
2. COLOR: NATURAL.

B	CHANGED FILE NUMBER	SM 05.31.01
A	MAT'L RMS-19 ADDED	J.L. 12.29.97
REV	DESCRIPTION	ENGR DATE

TITLE: TWIST-LOCK-HINGED-STANDOFF				DWG IN IN (MM)	
TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°	FILE # TLHS90	DWN: J.B.	APP:	FINAL	
	MAT'L: SEE NOTES	DT: 01-22-96	DT:	PART #	PRINT TYPE
	RE: RICHCO, INC.	RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060		TLHS90-300-01	CA