


CM2722R151R-10

PHYSICAL DIMENSIONS:

A	6.99	[.275]	± 0.10	[.004]
B	5.72	[.225]	± 0.10	[.004]
B ₁	6.73	[.265]		MAX
C	7.62	[.300]	± 0.13	[.005]
C ₁	8.40	[.330]		MAX.
D	2.41	[.095]	± 0.08	[.003]
E	0.89	[.035]	± 0.13	[.005]
E ₁	1.91	[.075]	± 0.13	[.005]
WIRE:				
T ₁	1.91	[.075]	± 0.25	[.010]
T ₂	0.38	[.015]		TYP.
T ₃	0.38	[.015]		TYP.



RoHS


ELECTRICAL CHARACTERISTICS:

Z @ 100MHz (Ω)	DCR (Ω)	Rated Current
Nominal	150	
Minimum	120	
Maximum	-	0.02
		5,000 mA


NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPEC. 13" REELS, 600 PCS per REEL.
2. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.
3. REF. CARRIER TAPE SPECIFICATION #CART2722-1P.
4. TERMINATION FINISH IS 100% TIN.
5. THIS PART HAS NO PIN POLARITY.
6. OPERATION TEMPERATURE (INCLUDING SELF-HEATING): -40 ~ +125°C.


Z vs. FREQUENCY (C,O,N)




Z, R, XL vs. FREQUENCY



LAND PATTERNS FOR REFLOW SOLDERING




EQUIVALENT CIRCUIT NO POLARITY



UNCONTROLLED DOCUMENT

RECOMMENDED SOLDERING CONDITIONS



DIMENSIONS ARE IN mm (INCHES).

This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.



D	ADD NOTE 6	08/30/12	QIU	PROJECT/PART NUMBER:	REV	PART TYPE:	DRAWN BY:
C	UPDATE COMPANY LOGO & ROHS SYMB. ADD EQUIVALENT CIRCUIT	01/29/09	JRK	CM2722R151R-10	D	ASSEMBLY	JRK
B	UPDATE COMPANY LOGO	05/18/07	JRK	DATE: 5/26/04	SCALE: NTS	SHEET:	
A	ORIGINAL DRAFT	5/26/04	JRK	CAD #	TOOL #		1 of 2
REV	DESCRIPTION	DATE	INT	CM2722R151R-10-D-1	H0275-1		