


HB-2X2-M-BLIND

~25° medium beam without centre screw hole
for easier potting


TECHNICAL SPECIFICATIONS:

Dimensions	50x50 mm
Height	8.5 mm
Fastening	glue, pin
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	9.3 kg
Quantity in Box	800 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
HB-2X2-M-BLIND	Lens array	PMMA	clear



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	C13239	HB-2X2-M-BLIND	PMMA	

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L



Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE
HB-2X2-M-BLIND

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy."


SIZE
A4 **C13239**

SCALE 1:1 WEIGHT SHEET 1/1



PHOTOMETRIC DATA (MEASURED):





LED XP-G
 FWHM 31.0°
 Efficiency 91 %
 Peak intensity 3.100 cd/lm
 Required components:




LED XP-G2
 FWHM 33.0°
 Efficiency 93 %
 Peak intensity 3.400 cd/lm
 Required components:



LED XT-E
 FWHM 25.0°
 Efficiency 92 %
 Peak intensity 3.700 cd/lm
 Required components:




LED H35C1 (LEMWA33)
 FWHM 29.0°
 Efficiency 91 %
 Peak intensity 3.400 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):




LED LUXEON Q
 FWHM 26.0°
 Efficiency 94 %
 Peak intensity 3.600 cd/lm
 Required components:




LED LUXEON Z ES
 FWHM 21.0°
 Efficiency 91 %
 Peak intensity 5.640 cd/lm
 Required components:



LED NVSxx19B/NVSxx19C
 FWHM 29.0°
 Efficiency 91 %
 Peak intensity 3.100 cd/lm
 Required components:





LED Oslon Square PC
 FWHM 30.0°
 Efficiency 91 %
 Peak intensity 3.400 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LH351Z
 FWHM 32.0°
 Efficiency 93 %
 Peak intensity 2.900 cd/lm
 Required components:





SEAGULL SEMICONDUCTOR

LED Z5M1/Z5M2
 FWHM 30.0°
 Efficiency 90 %
 Peak intensity 3.400 cd/lm
 Required components:




Leading Innovation >>>

LED TL1L4
 FWHM 25.0°
 Efficiency 85 %
 Peak intensity 3.500 cd/lm
 Required components:



TRIDONIC


LED RLE G1 49x121mm 2000lm xxx EXC OTD
 FWHM 29.0°
 Efficiency 94 %
 Peak intensity 3.000 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):


TRIDONIC

LED RLE G1 49x133mm 2000lm xxx EXC OTD
FWHM 29.0°
Efficiency 94 %
Peak intensity 3.000 cd/lm
Required components:




TRIDONIC

LED RLE G1 49x223mm 4000lm xxx EXC OTD
FWHM 29.0°
Efficiency 94 %
Peak intensity 3.000 cd/lm
Required components:



TRIDONIC


LED RLE G1 49x245mm 4000lm xxx EXC OTD
FWHM 29.0°
Efficiency 94 %
Peak intensity 3.000 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED Oslon Square Gen3
FWHM 32.0°
Efficiency 93 %
Peak intensity 3.970 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)