

Screw connection - WP-GA HF IP66 M40 BK - 3240929

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, metric thread, IP66 protection, angled

The figure shows the WP-GA HF IP66 M10 BK version

Key Commercial Data

| | |
|------------------------|----------|
| Packing unit | 1 STK |
| Minimum order quantity | 10 STK |
| Custom tariff number | 39174000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------------|---------------------|
| Length (b) | 67 mm |
| Width (a) | 44 mm |
| Height | 67.5 mm |
| Diameter | 45.00 mm |
| Outside diameter | 34.50 mm |
| Cable diameter | 34.5 mm ... 34.5 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 115 °C |
| Degree of protection | IP66 |

General

| | |
|--|--|
| Color | black |
| Type | Angled |
| | Outer thread |
| Components | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94 | HB |
| Material | PA |

Screw connection - WP-GA HF IP66 M40 BK - 3240929

Technical data

Standards and Regulations

| | |
|--|----|
| Connection in acc. with standard | UL |
| Flammability rating according to UL 94 | HB |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27141131 |
| eCl@ss 4.1 | 27141131 |
| eCl@ss 5.0 | 27141131 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC001178 |
| ETIM 5.0 | EC001178 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121411 |
| UNSPSC 12.01 | 39121411 |
| UNSPSC 13.2 | 39121411 |

Approvals

Approvals

Approvals

UL Recognized / VDE Zeichengenehmigung / LR




Ex Approvals

Screw connection - WP-GA HF IP66 M40 BK - 3240929

Approvals

Approvals submitted

Approval details



Accessories

Accessories

Corrugated pipe

Protective hose - WP-PA HF 42,5 BK - 3241089



Polyamide protective hose, inflammability class V0, UV resistant, 1 Pcs. / Pkt. = roll à 25 m

Protective hose - WP-PA HF-HB 42,5 BK - 3240844



Polyamide protective hose, inflammability class HB, UV resistant

Mounting material

Screw connection - WP-GA HF IP66 M40 BK - 3240929

Accessories

Protective hose fixing bracket - WP-BASE A M40 - 3241087



Fixing bracket for protective sleeves, fixed with two screws