NUMBER 69957











ENLARGED VIEW OF CRIMPS

"G" DIM. AT POS. #1		"C" DIM.	
GO	NO GO	GO	NO GO
.030	.050	.088	.095

1	38043	LEVER-TOGGLE	21
2	38039	LINK-TOGGLE	20
2	39207	PIN-ADJUSTMENT	19
6	39208	RING	18
2	38779	SPACER	17
2	38761	PIN-RETAINING	16
6	21045-3	RING-RETAINING	15
1	38783	PIN-RETAINING	14
2	38807	PIN-RETAINING	13
4	21045-6	RING-RETAINING	12
1	302994	STOP-HOUSING	11
1	301201	SPRING	10
1	1-45750-0	ANVIL	9
1	9-305927-1	SCREW	8
1	303542	LOCATOR	7
1	1-45751-1	INDENTER	6
1	3-306321-3	LINK	5
1	39085	PIN-PIVOT	4
1	47960	INDENTER-INSULATION	3
1	47961	ANVIL-INSULATION	2
1	6-306321-3	LINK	1
QUAN. REQUIRED PER ASSEMBLY	NUMBER	NAME	REMARKS ITEM NO.

©1969 BY AMP INCORPORATED. ALL RIGHTS RESERVED.
AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

CUSTOMER COPY REFERENCE ONLY

DR P. Ritzinger 12-12-69
CHK E. J. Hanks 1-7-70
DE
APP E. J. Hanks 1-7-70

MATERIAL AND FINISH + +
WIRE – RANGE – INSULATION 24-20 + +
TOLERANCE EXCEPT AS NOTED ± .015 ± 1° 0'
SCALE 1=1

AMP INCORPORATED HARRISBURG, PENNA.
CLASS + +
TYPE "C" PRE INSULATED DIAMOND GRIP
LOC M C NO. 69957 REV A

NAME PNEUMATIC HEAD ASS'Y MOD A

DESCRIPTION 69957

LTR	REVISION RECORD	ECN	BY	DATE
A	RELEASED	–	PP	12-15-69

DIMENSIONS IN INCHES DO NOT SCALE PRINT

Sc