



⑥规格 Specifications

额定负荷 Ratings	DC 30 V 0.3 A
初期接触电阻 Initial Contact Resistance	30 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric	AC 500 V (50~60HZ) 60 Sec.

操作力 Operating Force (gf)	A → B	B → A
	C → B	B → C
负荷寿命 Operating Life With Load	150±50	200±100
	10,000	次 Cycles

6	弹片 SPRING	C5210R	1	NATURAL	A01	POM → PA 见⑥	方勇	06-04-12
5	端子 TERMINAL	C2680R⑥	4	Ag PLATED		ADD: 规格 Specifications 见⑥		
4	基板 TERMINAL BASE	PHENOL RESIN	1	YELLOW		C2680R-EH → C2680R 见⑥		
3	接触片 CONTACT	C5210R⑥	1	Ag CLAD		C5210R-EH/Ag CLAD → C5210R 见⑥		
2	胶柄 KNOB	PA⑥	1	G 2 - 6	01		赖立辉	29 MAY 01
1	铁壳 FRAME	S P T E	1	NATURAL	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
序 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	DWG NO. ITEM1919			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	SIDE KNOB SLIDE SWITCH		ITEM NO	SK-13D08-G E		
UNDER 1	± 0.10	DRAWN	方勇	06-04-12	VERSION	A01	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	张念明	06-04-12	SCALE		UNIT	mm
OVER 10	± 0.50	APPROVED	林高全	06-04-12	PROJECTION			

COMAX ELECTRONICS (HUIZHOU) CO.,LTD.