



Directive 2002/95/EC RoHS compliant

plating pos. 2	part no.
GOLD FLASH over NICKEL	<b>132A13019X</b>
min. 20µin HARD GOLD over min. 50µin NICKEL	<b>132B13019X</b>
min. 30µin HARD GOLD over min. 50µin NICKEL	<b>132C13019X</b>

pos	qty	description	material	plating
3	1	RETAINING RING	COPPER ALLOY	NICKEL PLATED
2	1	MATING SIDE	COPPER ALLOY	SEE TABLE
1	1	REAR SIDE	COPPER ALLOY	TIN PLATED

partlist				
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance	ISO 2768-m	dim. in mm	scale: 8:1
	material:	SEE PARTLIST		
	date	name	title:	
	drawn	23.03.98	Barcinski	
	appd.	23.03.98	Mickenbecker	
norm				HIGH POWER CONTACT FEMALE SOLDER PIN 90°, d=2.85, 20A D-SUB COMBINATION
d-old				dwg no: 13K11F6A DIN-A3 sh: 1
1 x b	A4680	06.03.2013	K.H.	part no: SEE TABLE
a	Original			
rev.	description	date	name	

