

SPECIFICATION CONTROL DRAWING


55PC1152

TITLE FIVE CONDUCTOR CABLE, SHIELDED, JACKETED, 600 VOLT

Date 06-13-00

Revision A

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CONSTRUCTION DETAILS									
PART NUMBER	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
			LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC1152-24-*	24	38	.0060	.0080	.120	.133	.145	17.36	18.03
55PC1152-22-*	22	38	.0060	.0080	.136	.150	.163	23.08	23.84
55PC1152-20-*	20	38	.0065	.0085	.158	.173	.188	32.14	33.09
55PC1152-18-*	18	38	.0065	.0085	.183	.200	.217	45.04	46.20
55PC1152-16-*	16	38	.0070	.0090	.202	.222	.241	55.72	57.17
55PC1152-14-*	14	38	.0075	.0095	.244	.265	.285	81.33	83.20
55PC1152-12-*	12	36	.0080	.0100	.298	.324	.349	124.41	126.93

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
 Maximum continuous conductor temperature
 VOLTAGE RATING: 600 volts (rms)
 DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz
 CROSSLINKING PROOF TEST: 300 ± 3°C for 1 hour
 JACKET COLOR: White preferred
 JACKET ELONGATION AND TENSILE STRENGTH:
 Elongation, 50% (minimum)
 Tensile Strength, 5000 lbf/in² (minimum)
 JACKET FLAWS:
 Spark Test, 1000 volts (rms), 100% test
 Impulse Dielectric Test, 6.0 kV (peak), 100% test

SHIELD COVERAGE: 85% (minimum)
 VOLTAGE WITHSTAND TEST (POST ENVIRONMENTAL):
 1000 volts (rms), 60 Hz, 1 minute

PART NUMBER:
 The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.
 Example: AWG 22, red, blue, yellow, green and black component wires; white jacket: 55PC1152-22-2/6/4/5/0-9

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF ADVERTISEMENT FOR BID.

300 Constitution Drive, Menlo Park, California 94025
 1-800-2 RAYCHEM FAX: 650-361-6297