



- 注1 1REEL:30000 PIECES PER REEL.  
 注2 STYLE OF REEL AND BOX SHOWS IN FIGURE.  
 注3 MAXIMUM NUMBER OF REEL PER BOX:5REEL  
 注4 FOR THE ADJUSTMENT OF THE APPLICATOR, ALWAYS USE THE APPLICABLE CABLE TO CONFIRM THE CRIMP CONDITIONS.

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
1	PHOSPHOR BRONZE						CONTACT AREA : Au PLATING 0.05 $\mu$ m MIN UNDER PLATING : Ni PLATING 1 $\mu$ m MIN

  

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	20 : 1	△				

  

<b>HRS</b> HIROSE ELECTRIC CO., LTD.	APPROVED : TS. SAKATA	09.06.02	DRAWING NO.	EDC3-320119-00
	CHECED : MN. KENJO	09.06.02	PART NO.	DF50-2830SCFA
	DESIGNED : TT. OHSAKO	09.06.01	CODE NO.	CL665-0002-0-00
	DRAWN : TT. OHSAKO	09.06.01		