



NOTES:

1. METALHELLS: STAINLESS STEEL;
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
PLATING: 50µin HARD GOLD over min. 50µin NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. CONNECTOR IS PART MARKED: DSSGXSMJD01X CONEC ABC

Directive 2002/95/EC
„RoHS“
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
a	Origin		
rev.	description	date	name

tolerance ISO 2768-m		 dim. in mm
date	name	
drawn	03.03.2008	Sonnenberg
appd.	03.03.2008	Kühle
norm		
d-old		

scale: 2:1 (5:1)	
material: SEE NOTES	
D-SUB MALE 9pos. SOLDER CUP	
dwg no:	Inventor 10
16K1A2250	
part no:	DSSGXSMJD01X
DIN-A3	sh: 1

