


C4AT, Film, Metallized Polypropylene, Power, 3.3 uF, 5%, 275 VAC, 450 VDC, 70C, Lead Spacing = 27.5mm



**Dimensions**

L	32mm NOM
H	33mm NOM
T	18mm NOM
S	27.5mm +/-0.4mm
S1	5.1mm +/-0.4mm
LL	6mm -2mm
F	1.2mm NOM

**Packaging Specifications**

<b>Packaging:</b>	Bulk, Bag
<b>Packaging Quantity:</b>	80

**General Information**

<b>Supplier:</b>	KEMET
<b>Series:</b>	C4AT
<b>Dielectric:</b>	Metallized Polypropylene
<b>Style:</b>	Radial
<b>Features:</b>	Switching
<b>RoHS:</b>	Yes
<b>Lead:</b>	4 Wire Leads

**Specifications**

<b>Capacitance:</b>	3.3 uF
<b>Capacitance Tolerance:</b>	5%
<b>Voltage AC:</b>	275 VAC
<b>Voltage DC:</b>	450 VDC
<b>Temperature Range:</b>	-40/+85C
<b>Rated Temperature:</b>	70C
<b>Dissipation Factor:</b>	0.05%
<b>Max dV/dt:</b>	82 V/us
<b>Resistance:</b>	2.9 mOhms (100kHz)
<b>Ripple Current:</b>	21 Amps (100kHz 70C), 269 Amps (Peak)