

Crimping pliers - CRIMPFOX DUO 10 - 1031721

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimping pliers, type of contact: Insulated and uninsulated ferrules, standards/specifications: DIN 46228-1, DIN 46228-4, min. cross section: 0.14 mm², max. cross section: 10 mm², for TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, rotating die, lateral and frontal insertion, compression: Trapezoidal crimp, black

Why buy this product

- Crimping at difficult-to-access points, thanks to rotating die
- Comfortable to use, thanks to low grip span with optimum manual force progression
- Suitable for TWIN ferrules, thanks to continuous automatic adjustment
- Large cross section range from 0.14 mm² ... 10 mm²
- Process reliability, thanks to pressure lock and self-adjusting die



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626535371

Technical data

Dimensions

Length (b)	180 mm
Width (a)	65 mm
Height (c)	25 mm

General

Color	black
Compression	Trapezoidal crimp
Type of contact	Insulated and uninsulated ferrules
Designation	Crimping position 1
Min. cross section	0.14 mm ²
Max. cross section	10 mm ²
AWG min	26
AWG max	8

Crimping pliers - CRIMPFOX DUO 10 - 1031721

Technical data

General

Weight	305 g
Min. cross section	0.14 mm ²
Max. cross section	10 mm ²

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU x- DE.xx08.B.02974
-----	---	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>