


Note:


- Material: Housing-polycarbonate, clear Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder. Over 2.54mm[.000100] thick nickel underplate.

SEC: $\triangle = \triangle$

P1	P2
2 BLACK	5
3 RED	4
4 GREEN	3
5 YELLOW	2



Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/4/W-5	A	1,525±20(5ft)	White	1,525-1,535mm
AT-S-26-6/4/W-7	B	2,135±30(7ft)	White	2,135-2,145mm
AT-S-26-6/4/W-10	C	3,050±60(10ft)	White	3,050-3,060mm
AT-S-26-6/4/W-12	D	3,660±60(12ft)	White	3,660-3,670mm
AT-S-26-6/4/W-14	E	4,270±60(14ft)	White	4,270-4,280mm
AT-S-26-6/4/W-25	F	7,625±100(25ft)	White	7,625-7,635mm
AT-S-26-6/4/W-50	G	15,250±150(50ft)	White	15,250-15,260mm

Scale	Free				Date	Name	Title
TOLERANCE					Drawn	08.07.13	Wilson
X.	±X				Approved	08.07.13	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name		
						1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us	Title Modular cable - Straight 6P4C 50µ", 26AWG, White, 5-50 feet ASSMANN WSW-No. AT-S-26-6/4/W-xx Drawing-No. rev00 Replace Sheet 1/1

