




NOTES:

1. MATERIAL: PVC, SOFT (RMS-55).
2. COLOR: BLUE, TRANSLUCENT.
3. FOR "SPASH PROOF SEAL"
RECOMMENDED WIRE OD=.088 TO .120
(2.2 TO 3.1).

G	FILE NO. WAS ISFPR	SM 10.30.02	TITLE: INSULATING SLEEVE FOR PIN RECEPTACLE				 	DWG IN	
F	RMS-55 WAS RMS-126	RG 09.26.01	IN (MM)		FINAL				
E	ADDED RMS-126 AND CHANGED FILE NO.	SM 06.26.01	TOLERANCES	FILE # 215010	DWN: P.B.	APP:	PART #		
D	DIM .30 (7.6) CHANGED TO REF.	JL 4/12/99	UNLESS NOTED	MAT'L: SEE NOTES	DT: 03-23-95	DT:	215010		
C	DIMENSIONS UPDATED	J.L. 8.28.98	.XX=±.010	RE: RICHCO, INC.	RICHCO INC.		PRINT		
B	CONV. TO ACAD; COLOR CHANGE-SEE ECN 128	FL 03.23.95	.XXX=±.005	PO BOX 804238, CHICAGO, 60680		TYPE		CA	
A	INSIDE DIA. .085 WAS .09	JP 09.12.90	FRAC=±1/64	(773) 539-4060		CA			
REV	DESCRIPTION	ENGR DATE	ANG=±1'						