

Smart Technology. Delivered.™

MAF94005 - MAF94006 MAF94022 - MAF94021

5

2400-2500 / 4900-6000 MHz

Knuckle **Elbow**

> **Fixed** Elbow

External Antenna: Snap-in/Captive


Specifications:

- Covers 2.4 to 2.5 GHz for 802.11b, and 4.9 to 6 GHz for 802.11a and all US, European, and Japanese WLAN applications
- Fixed Right-Angle design for Access points, gateways, & portable devices
- Coaxial cable pigtail with various connector choices
- Omni-directional patterns at all frequencies with increased gain in upper bands for optimal coverage

Frequency	2.4 - 2.5 GHz		
	4.9 – 6 GHz		
Gain	2.5 dBi (2.45 GHz)		
	3.8 dBi (4.9 GHz)		
	4.6 dBi (5.25 GHz)		
	5.2 dBi (5.75 GHz)		
Polarization	Vertical, Omni-directional		
Nominal Impedance	50 ohms		
VSWR	2:1 max across all bands		
Size	4.9" (180° straight) or 4.25" (90° bent) x .6" dia.		

Cables and Connectors:

Model #	Part #	Elbow	Connector	Cable	
WTC2450-IP04-F	MAF94005	Fixed	IPEX MHF	100mm, Ø 1.13mm	
WTC2450-IP04-K	MAF94006	Knuckle	IPEX MHF	100mm, Ø 1.13mm	
WTC2450-FL04-F	MAF94022	Fixed	Flying lead	100mm RG-178	
WTC2450-FL04-K	MAF94021	Knuckle	Flying lead	100mm RG-178	



Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: IAS-AsiaSales@lairdtech.com

Middle East & Affrica: +44.1628.858941 IAS-

MEASales@lairdtech.com www.lairdtech.com